



The article is no longer in our assortment.

Features:

Logistic**OMNITRONIC DD-5220L Turntable bk**

Direct drive DJ turntable "Ultra Torque" with switchable phono/line output

- Direct drive high-torque motor Quartz-controlled for highest speed precision
- 3 speeds (33 1/3, 45 and 78 RPM), pitch control $\pm 10\%$, $\pm 20\%$, $\pm 50\%$
- Selectable quartz-controlled pitch lock
- Quick start
- Adjustable start/stop time
- 2 large start/pause buttons
- Reverse run
- Plug-in LED target lamp
- Adjustable anti-skating
- Tone arm height adjustable
- Shock-absorbing and adjustable feet
- Switchable phono/line output
- Extremely resonance-free due to optimally combined components
- Platter and motor are directly connected for highest stability
- Recessed connections for easy case mounting
- Delivery includes headshell, slipmat and RCA cable
- Dust cover and pick-up system optionally available
- Pitch range: $\pm 10\%$, $\pm 20\%$, $\pm 50\%$

Package contents

- 1 x device, 1 x power cord, 1 x turntable platter, 1 x felt mat, 1 x shellset, 1 x balance weights, 1 x plug (male), 1 x adapter, 1 x RCA cable, 1 x user manual

OMNITRONIC Dust Cover for DD-5250/DD-5220L<p class='attributgroup'>Package contents

- 1 x lid

ROADINGER Turntable Case Tour Pro black -B-

Carrying case

- High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding
cover with foam padding
- Removable cover
- Aluminum profile frames 25mm with rounded edges
- Hinged, chromium plated case handle
- 2 high-quality butterfly locks with shut-off function
- Rubber feet
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 18,57 kg

OMNITRONIC DD-5220L Turntable bk

Power supply:	230 V AC, 50 Hz
Power consumption:	15,00 W
Protection class:	Protection class I
Power connection:	Fixed power supply cord with Euro plug
Frequency range:	20 - 20000 Hz
Drive type:	Quarz-controlled direct drive Brushless DC motor
Drive:	Initial torque: 4,5 kg/cm Start time: 0.2 - 6 sec, adjustable Stop time: 0.2 - 6 sec, adjustable Speed change time: <1s 1kHz 5cm/sec
Wow and flutter:	<0,1 % WRMS
Rumble:	60 dB DIN B
Speed:	33 RPM; 45 RPM; 78 RPM forward/backward
Tone arm:	S-shape with Cardan's suspension Length: 230 Tonearm heigh: 8 - 10.5 mm adjustable Overhang: 15 mm Stylus pressure: 0-4 g, adjustable
Output level:	Phono 1,5-3,6 mV/ 1 kHz 5 cm/sec Line 90-216 mV/ 1 kHz 5 cm/sec
Connections:	Output: line/phono via 1 x stereo RCA
Pitch range:	±10%, ±20%, ±50%
Dimensions:	Width: 45 cm Depth: 35,3 cm Height: 15,6 cm

Weight:	11,30 kg
Turntable platter	
Material:	Metal
Dimensions:	Diameter: Ø 33,2 cm
Weight:	1,425 kg

OMNITRONIC Dust Cover for DD-5250/DD-5220L

Color:	Clear
Dimensions:	Width: 45,7 cm Depth: 35,9 cm Height: 8,1 cm
Weight:	0,77 kg

ROADINGER Turntable Case Tour Pro black -B-

Maximum load:	20 kg
Removable covers:	1 pc/pcs
Aluminum profile frames:	25 mm
Case handle:	1 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Transport aid:	Rubber feet
Material:	Plywood multi-layer glued, 7 mm
Color:	Black, laminated
Device compartment:	45 cm x 35,5 cm x 12 cm
Dimensions:	Width: 53,5 cm Depth: 45,5 cm Height: 23 cm
Weight:	6,50 kg