

OMNITRONIC LH-020 3-channel Mic Mixer

3-channel microphone mixer

Art. No.: 10355020

GTIN: 4026397169041



List price: 141.61 €

incl. 19% VAT.

Features:

- Compact mixer to mix 3 microphones to 1 line output, with individual level control
- 3 microphone input channels with separate level controls, switchable phantom power and low cut
- 1 master output with line level, clip LED
- 1 headphones output (6.3 mm jack)
- Inputs and output via balanced XLR connectors
- Desktop console housing

Package contents

- 1 x user manual, 1 x external mains adapter, 4 x foot, 1 x mixer

Logistic

EAN / GTIN: 4026397169041

Weight: 0,90 kg

Length: 0.23 m

Width: 0.13 m

Height: 0.08 m

Technical specifications:

| | |
|--------------------|---|
| Power supply: | 12V DC 150 mA Or 18V DC |
| Pin configuration: | Inside - / outside + |
| Protection class: | Protection class III |
| Power connection: | Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided) Battery/battery pack |
| Battery: | 2 x 9.0 V E block (not included) |

| | |
|-------------------|--|
| Frequency range: | 25 - 16000 Hz |
| S/N ratio: | >75 dB |
| THD: | <0,02 % at 1 kHz |
| Phantom power: | Or 18 V DC |
| Impedance: | Input: 600 Ohm 600 Ohm |
| Gain: | 60 dB |
| Housing color: | Silver |
| Control elements: | Power switch, low cut switch, phantom power switch, level control per channel |
| Status LED: | Power, clip |
| Connections: | Input: microphone via 3 x 3-pin XLR Output: microphone via 1 x 3-pin XLR Output: headphones via 1 x 6.3 mm jack socket (stereo) mounting version |
| Input channels: | 3 x mono via XLR, channel control via rotary dial |
| Max. level: | Input: -14 dB Output: +14 dB |
| Housing design: | Desktop console housing |
| Dimensions: | Width: 14,3 cm Depth: 9,3 cm Height: 4,5 cm |
| Weight: | 0,76 kg |