

## **OMNITRONIC DJP-900P Class D Amplifier**

Compact stereo mixing amplifier with player + Bluetooth, 2 x 460 W / 4 ohms

Art. No.: 10451603 GTIN: 4026397641110









# The article is no longer in our assortment.

#### Features:

- For quick-access music playback control in restaurants, fitness studios, retail locations etc.
- Built-in audio player with Bluetooth receiver
- Extremely low weight and height due to integrated switch mode power supply
- 2 operating modes can be selected (stereo or bridge/100V)
- Speaker switch-on delay and auto limiters
- 1 mono microphone input with volume control on the front panel
- Audio source selector
- Extensive protective circuits
- Rugged steel chassis with aluminum front panel
- The device is cooled by passive convection cooling
- Desktop console housing
- (19") 48.3 cm rack installation possible 1 U

### audio player

- Control via Bluetooth
- Bluetooth: operating range up to 10m
- 2.4 GHz license-free worldwide

#### Package contents

1 x device, 1 x power cord, 1 x user manual, 1 x declaration of conformity, 2 x mounting bracket

### **Technical specifications:**

Power supply:	230 V AC, 50 Hz
Power consumption:	140 W 1/8 power
Output power:	2 x 460 W RMS (4 ohms)

## Logistic

EAN / GTIN: 4026397641110

Weight: 2,95 kg Length: 0.34 m Width: 0.29 m Heigth: 0.08 m

2 x 240 W RMS (8 ohms) Max. 260 W Max. 900 W Power connection: Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) 20 - 20,000 Hz Frequency range: S/N ratio: >100 dB THD: <0,05 % at 1 kHz Cooling: Passive convection cooling Impedance: 4 ohms; 8 ohms; 16 ohms; public address systems 100V Impedance: Input: 20 kOhm, bal. Input: 10 kOhm, bal. Class D Circuitry: Slew rate: >14 V/µs Damping factor: >300 Control elements: Power switch, source selector, tone control, level control, mode switch (stereo / bridged/100V) Controls: Softstart; short-circuit; overheat; overload; DC voltage; VHF Status LED: Power Connections: Input: microphone via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: line via 4 x stereo RCA Input: line via 1 x 3.5 mm jack (stereo) mounting version Output: speaker via 1 x screw terminal Output: rec. via 1 x stereo RCA Equalizer: Master: 1 x 2-band tone control stereo Input sensitivity: 1 V Material: Metal Housing design: Desktop console housing (19") 48.3 cm rack installation possible 1 U Dimensions: Width: 24,1 cm Depth: 25,6 cm Height: 4,45 cm Weight: 2,54 kg

Audio player
Control:

Audio player:

Frequency band:

Available storage media:

Music format:

Range:

Bluetooth

2.4 GHz

USB + SD + Bluetooth

MP3, WMA; WAV

Bluetooth: range up to 10m

USB devices/SD cards max. 32GB (FAT 16/32)