

OMNITRONIC OD-4T Wall Speaker 100V black 2x

Weather-proof wall speaker pair (IP65) with 4" woofers and 30 W RMS

Art. No.: 11036914

GTIN: 4026397543568









List price: 95.08 €

incl. 19% VAT.

Features:

- 2-way system with 10 cm woofer (4") and 1.3 cm tweeter (0.5")
- Durable plastic cabinet with metal grille and cover for the connectors
- Power selector switch with 8 ohms operating position
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles
- Suitable for outdoor use IP65
- 2 pieces per set
- For application areas such as: Trade fair and shop fitting; restaurants, bars and hotels; product presentations and lectures

Package contents

2 x compact cabinet speaker, 2 x mounting bracket, 4 x knurled screw, 1 x user manual

Technical specifications:

IP65
Program: 60W (8 ohms)
Rated: 30W RMS (8 ohms)
Rated: 16W RMS (100V PA)
100 - 20000 Hz
88 dB
100 dB (100V PA); 106 dB (8 ohms)
170° x 170°

Logistic

EAN / GTIN: 4026397543568 Weight: 3,94 kg Length: 0.33 m Width: 0.15 m Heigth: 0.21 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Impedance:	Public address systems 100V; 8 ohms
Attachment system:	Panning and tilting mounting bracket for ceiling or wall installation in most varying angles
Power tapping:	2W; 4W; 8W; 16W RMS via selector switch switchable
Connections:	Input: speaker via screw terminal
Speaker:	1 x woofer 4"
	1 x dome tweeter 0,5"
Type of speaker:	Compact cabinet speaker
Dimensions:	Width: 12,5 cm
	Depth: 12,5 cm
	Height: 19,5 cm
Weight:	3,66 kg