

OMNITRONIC OD-6T Wall Speaker 100V black 2x

Weather-proof wall speaker pair (IP65) with 6,5" woofers and 50 W RMS

Art. No.: 11036926

GTIN: 4026397543667









List price: 172.55 €

incl. 19% VAT.

Features:

- 2-way system with 16.5 cm woofer (6.5") and 2.5 cm silk dome tweeter (1")
- Durable plastic cabinet with metal grille and cover for the connectors
- Power selector switch with 8 ohms operating position
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles
- Black aluminum grille
- Suitable for outdoor use IP65
- 2 pieces per set
- For application areas such as: Trade fair and shop fitting; restaurants, bars and hotels; product presentations and lectures

Package contents

2 x compact cabinet speaker, 2 x mounting bracket, 4 x knurled screw, 1 x user manual

Technical specifications:

IP classification:	IP65
Power:	Program: 100W
	50W RMS (8 ohms)
	Rated: 32W RMS (100V PA)
Frequency range:	50 - 20000 Hz
Sensitivity:	90 dB
Max. SPL:	105 dB (100V PA); 110 dB (8 ohms)
Dispersion angle:	170° x 170°

Logistic

EAN / GTIN: 4026397543667 Weight: 7,75 kg Length: 0.50 m Width: 0.23 m Heigth: 0.33 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Impedance:	Public address systems 100V; 8 ohms	
Attachment system:	Panning and tilting mounting bracket for ceiling or wall installation in most varying angles	
Power tapping:	4W; 8W; 16W; 32W RMS via selector switch switchable	
Control elements:	Level control	
Connections:	Input: speaker via screw terminal	
Speaker:	1 x woofer 6,5" Basket material: steel Dome tweeter 1"	
Type of speaker:	Compact cabinet speaker	
Material:	Plastic	
Color:	Black	
Dimensions:	Width: 19,5 cm Depth: 19 cm Height: 29 cm	
Weight:	7,10 kg	