

OMNITRONIC ODX-215TM Installation Speaker 100V dark gray

Weather-proof 15" wall speaker (IP56) with mount, 400 W RMS


Art. No.: 11036967 GTIN: 4026397703221











incl. 19% VAT.

Features:

- Well-balanced sound
- 2-way coaxial system with 38 cm woofer (15") and 4 cm tweeter (1.7")
- Power selector switch with 8 ohms operating position
- Screw terminals for parallel connection
- With mounting bracket
- Grey aluminum grille
- Suitable for outdoor use IP56
- For application areas such as: Sports centres/gyms; multi-purpose hall

Package contents

- 1 x top, 1 x mounting bracket, 1 x user manual, 6 x screw, 1 x safety eyelet, 1 x lid, 8 x washer

Logistic

EAN / GTIN: 4026397703221

Weight: 29,90 kg Length: 0.61 m Width: 0.59 m Heigth: 0.57 m Bulky product

Technical specifications:

IP classification:	IP56
Power:	Program: 800W Rated: 400W RMS
Frequency range:	50 - 18000 Hz
Sensitivity:	103 dB (1W/1m)
Max. SPL:	129 dB
Dispersion angle:	70° x 70°
Impedance:	8 ohms; public address systems 100V

Mounting bracket
75W; 150W; 300W; 400W RMS via selector switch switchable
Input: speaker via screw terminal
2100 Hz
1 x woofer 15"
Basket material: aluminum
Conematerial: cardboard/paper
Voice coil lows 3"
1 x compression tweeter highs 1"
Voice coil compression tweeter highs 1,7"
On ceiling/on wall speaker
4 mm
Grey
Width: 50 cm
Depth: 52 cm
Height: 50 cm
26,80 kg