

## PSSO MIMO-150A Active Stage Monitor

Ultra compact active monitor speaker (3 x 4", 150 W RMS)

Art. No.: 11038041

GTIN: 4026397720112



**List price: 534.31 €**

incl. 19% VAT.

### Features:

- Efficient class D amplifier with 150 watts power
- LAVOCE speaker
- High sound pressure and wide frequency range
- Low weight
- High-quality workmanship with birch multiplex, black, rubberized Polyurea coating
- Black metal grille with acoustic foam
- For application areas such as: Stage; concerts/FoH's; band/rehearsal room; mobile use
- Application possibility: Monitoring

#### Package contents

- 1 x device, 1 x user manual, 1 x power cord

### Logistic

EAN / GTIN: 4026397720112

Weight: 5,50 kg

Length: 0.41 m

Width: 0.25 m

Height: 0.19 m

### Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	270 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version
Power:	Rated: 150W RMS Program: 250W
Frequency range:	78 - 20000 Hz
Max. SPL:	119 dB

Dispersion angle:	30° x 60°
Attachment system:	2x M6 thread 2x M10 thread
Control elements:	Power switch, level control, tone control
Controls:	Limiter
Status LED:	Power, limit
Connections:	Input: line via 1 x 6.3-mm-jack (bal.) Input: microphone via 1 x 3-pin XLR Output: 1 x 3-pin XLR (M) mounting version
Speaker:	3 x full range loudspeaker 4" with ferrit magnet Basket material: steel Conematerial: cardboard/paper
Type of speaker:	Stage monitor
Type of construction:	Closed Box
Use of brands:	LAVOCE speaker
Material:	Birch multiplex
Color:	Black, rubberized Polyurea coating
Dimensions:	Length: 20 cm Width: 36 cm Height: 13 cm
Weight:	5,05 kg