

OMNITRONIC KPA-215A PA Cabinet active

Active 2-way speaker-system

Art. No.: 11038722

GTIN: 4026397200799



The article is no longer in our assortment.

Features:

- XLR and jack socket for direct connection with the signal source (line, mic)
- Line/Mic pad for input level adjustment
- Large mid-range horn with powerful driver
- Bi-amped for cristal clear playback
- Ideal as floor-monitor, standing, on a speaker stand or on a wall-mounting
- Strong protective grille for perfect protection
- Scratch-resistant plastic housing
- Compact speaker system for car transport
- Ideal for live music or discotheques
- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

EAN / GTIN: 4026397200799

Weight: 25,10 kg

Length: 0.55 m

Width: 0.41 m

Heigth: 0.76 m

Technical specifications:

Power supply: 230 V AC, 50 Hz

Power consumption: 510,00 W

Output power: Max. 510 W

Frequency range: 55 - 18000 Hz

Dimensions:
Width: 50 cm
Depth: 36 cm
Height: 73 cm

Weight: 22,80 kg

Dimensions (H x W x D):	730 x 500 x 360 mm
Speaker-system:	
Rated power:	250 W RMS
Program power:	500 W
Components:	38 cm woofer (15"), 2.5 cm horn (1")
Inputs:	XLR/jack
Dispersion angle:	90° x 40°
Maximum SPL:	120 dB
Impedance:	8 ohms
LF-amplifier:	
Maximum power output:	450 W / 4 ohms
Distortion:	0.1 %
HF-amplifier:	
Maximum power output:	50 W / 4 ohms
Distortion:	0.1 %