

## OMNITRONIC XKB-208A 2-way Speaker, active, Bluetooth

Active speaker with 8" woofer, 1" driver, 35 W RMS HF, 70 W RMS LF

Art. No.: 11038793

GTIN: 4026397628333



**List price: 196.35 €**

incl. 19% VAT.

### Description:

The speaker systems of the XKB series are high-performance active speaker systems in light-weight and rugged plastic cabinets. They can be flexibly used for permanent installations and professional live applications. The 2-way speaker systems are designed as full-range bass-reflex systems with separate power amplifiers for the high-frequency range and the low-frequency range featuring inputs for microphones and line sources and parallel outputs for coupling with other active speakers. The DSP (digital signal processor) features convenient application presets for quick sound contouring (models XKB-212A and XKB-215). The built-in Bluetooth player allows for streaming music wirelessly from smartphones or tablets via Bluetooth. The speakers systems are protected through limiters and extensive protective circuits. The enclosure offers multiple setup options (use as a floor monitor, wall or stand mounting).

### Features:

- Class D biamp amplifier (LF 70 W, HF 35 W)
- 2-way bass-reflex enclosure with 20 cm woofer and 2.5 cm driver
- 1 mic/line combo input (XLR/jack) with level control
- 1 line input (RCA) with level control
- Master control with 2-band EQ
- Control via Bluetooth
- Black metal grille with acoustic foam
- 3 Rugged carrying handles
- Application possibility: Standing; monitoring; on stand
- For application areas such as: Mobile use; rental; sports centres/gyms; mobile djs / entertainer

#### Package contents

- 1 x compact cabinet speaker, 1 x user manual, 1 x power cord, 1 x declaration of conformity

### Logistic

EAN / GTIN: 4026397628333

Weight: 7,60 kg

Length: 0.32 m

Width: 0.32 m

Height: 0.49 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	300 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power:	Program: 140W Rated: 35W RMS HF Rated: 70W RMS LF
Frequency range:	65 - 20000 Hz
Sensitivity:	94 dB
Dispersion angle:	90° x 50°
Control:	Bluetooth
Bluetooth device name:	Omnitronic KKB
Attachment system:	Flange: Ø 35mm
Circuitry:	Class D Biamp
Control elements:	Level control per channel, tone control, power switch, bypass/terminating resistor switch
Controls:	Limiter
Status LED:	Power, clip
Connections:	Input: microphone via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: line via 1 x stereo RCA Output: line via 1 x 3-pin XLR
Input channels:	1 x mono with mic-line switch via Combination socket (XLR/jack), channel control via rotary dial 1 x stereo via RCA or Bluetooth, channel control via rotary dial
Equalizer:	Master: 1 x 2-band tone control
Speaker:	1 x woofer 8" Basket material: steel Conematerial: cardboard/paper Voice coil lows 1,35" with ferrit magnet Voice coil compression tweeter highs 1"
Type of speaker:	Compact cabinet speaker
Type of construction:	Vented
Carrying handle:	3 pc/pcs
Material:	Plastic
Color:	Black
Dimensions:	Width: 26 cm Depth: 27 cm Height: 43 cm
Weight:	6,90 kg