

OMNITRONIC XKB-212A 2-way Speaker, active, DSP

Active speaker with 12" woofer, 1,35" driver, 60 W RMS HF, 300 W RMS LF

Art. No.: 11038795

GTIN: 4026397606485











List price: 355.81 €

incl. 19% VAT.

Features:

- Active 12/2 full range system for mobile live and DJ applications
- DSP-controlled biamp amplifier (LF class D, HF class A/B)
- 24-bit DSP with adjustable high-pass filter, parametric 3-band EQ and signal delay
- Built-in Bluetooth player for audio streaming from compatible Bluetooth devices such as smartphones, tablets and notebooks
- 2-way bass-reflex enclosure with 30 cm woofer and 3.5 cm titanium driver
- 2 mic/line inputs (XLR/6.3 mm jack) with separate level controls
- Control via Bluetooth
- LCD display

Protection class:

- Digital signal processor
- Black metal grille with acoustic foam
- 3 Rugged carrying handles
- Application possibility: Standing; monitoring; on stand
- DSP presets: LIVE; MUSIC; SPEECH; DJ; TRIPOD; MONITOR; WALL
- For application areas such as: Mobile use; rental; sports centres/gyms; mobile djs / entertainer Package contents
- 1 x compact cabinet speaker, 1 x power cord, 1 x user manual, 1 x declaration of conformity

Technical specifications: Power supply: 100-240 V AC, 50/60 Hz Power consumption: 800 W

Protection class I

Logistic

EAN / GTIN: 4026397606485 Weight: 16,85 kg Length: 0.44 m Width: 0.40 m Heigth: 0.68 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

•	nnector (M) mounting ord with safety plug
Sensitivity:95 dBDSP:Digital signal processoDSP presets:LIVE; MUSIC; SPEECH MONITOR; WALLDispersion angle:90° x 50°Control:BluetoothBluetooth device name:OmnitronicAttachment system:Flange: Ø 35mmCircuitry:Class D BiampDisplay type:LCD displayControl elements:Master control, encodeControls:LimiterStatus LED:Power, signal, limitConnections:Output: line via 1 x 3-piInput channels:2 x mono with mic-line socket (XLR/jack), chanceEqualizer:Master: 1 x 3-band toneSpeaker:1 x woofer 12" Voice coil lows 2,4" with 	
DSP:Digital signal processorDSP presets:LIVE; MUSIC; SPEECH MONITOR; WALLDispersion angle:90° x 50°Control:BluetoothBluetooth device name:OmnitronicAttachment system:Flange: Ø 35mmCircuitry:Class D BiampDisplay type:LCD displayControl elements:Master control, encodeControls:LimiterStatus LED:Power, signal, limitConnections:Output: line via 1 x 3-piInput channels:2 x mono with mic-line socket (XLR/jack), chaitSpeaker:1 x woofer 12" Voice coil lows 2,4" wit Voice coil compressionType of speaker:Compact cabinet spealType of construction:VentedCarrying handle:3 pc/pcsMaterial:PlasticColor:Black	
DSP presets: LIVE; MUSIC; SPEECI MONITOR; WALL Dispersion angle: 90° x 50° Control: Bluetooth Bluetooth device name: Omnitronic Attachment system: Flange: Ø 35mm Circuitry: Class D Biamp Display type: LCD display Control elements: Master control, encode Controls: Limiter Status LED: Power, signal, limit Connections: Output: line via 1 x 3-pi Input channels: 2 x mono with mic-line socket (XLR/jack), chai Equalizer: Master: 1 x 3-band ton Speaker: 1 x woofer 12" Voice coil lows 2,4" wit Voice coil compression Type of speaker: Compact cabinet speal Type of construction: Vented Carrying handle: 3 pc/pcs Material: Plastic Color: Black	
MONITOR; WALLDispersion angle:90° x 50°Control:BluetoothBluetooth device name:OmnitronicAttachment system:Flange: Ø 35mmCircuitry:Class D BiampDisplay type:LCD displayControl elements:Master control, encodeControls:LimiterStatus LED:Power, signal, limitConnections:Output: line via 1 x 3-piInput channels:2 x mono with mic-line socket (XLR/jack), chaitSpeaker:1 x woofer 12" Voice coil lows 2,4" wit Voice coil compressionType of speaker:Compact cabinet spealType of construction:VentedCarrying handle:3 pc/pcsMaterial:PlasticColor:Black	r
Control:BluetoothBluetooth device name:OmnitronicAttachment system:Flange: Ø 35mmCircuitry:Class D BiampDisplay type:LCD displayControl elements:Master control, encodeControls:LimiterStatus LED:Power, signal, limitConnections:Output: line via 1 x 3-piInput channels:2 x mono with mic-line socket (XLR/jack), chailEqualizer:Master: 1 x 3-band toneSpeaker:1 x woofer 12" Voice coil lows 2,4" wit Voice coil compressionType of speaker:Compact cabinet speadType of construction:VentedCarrying handle:3 pc/pcsMaterial:PlasticColor:Black	H; DJ; TRIPOD;
Bluetooth device name: Omnitronic Attachment system: Flange: Ø 35mm Circuitry: Class D Biamp Display type: LCD display Control elements: Master control, encode Controls: Limiter Status LED: Power, signal, limit Connections: Output: line via 1 x 3-pi Input channels: 2 x mono with mic-line socket (XLR/jack), chai Equalizer: Master: 1 x 3-band tone Speaker: 1 x woofer 12" Voice coil lows 2,4" wit Voice coil compression Voice coil compression Type of speaker: Compact cabinet spead Type of construction: Vented Carrying handle: 3 pc/pcs Material: Plastic Color: Black	
Attachment system:Flange: Ø 35mmCircuitry:Class D BiampDisplay type:LCD displayControl elements:Master control, encodeControls:LimiterStatus LED:Power, signal, limitConnections:Output: line via 1 x 3-piInput channels:2 x mono with mic-line socket (XLR/jack), charEqualizer:Master: 1 x 3-band toneSpeaker:1 x woofer 12" Voice coil lows 2,4" with Voice coil compressionType of speaker:Compact cabinet spealType of construction:VentedCarrying handle:3 pc/pcsMaterial:PlasticColor:Black	
Circuitry: Class D Biamp Display type: LCD display Control elements: Master control, encode Controls: Limiter Status LED: Power, signal, limit Connections: Output: line via 1 x 3-pi Input channels: 2 x mono with mic-line socket (XLR/jack), chait Equalizer: Master: 1 x 3-band tone Speaker: 1 x woofer 12" Voice coil lows 2,4" wit Voice coil compression Type of speaker: Compact cabinet spead Type of construction: Vented Carrying handle: 3 pc/pcs Material: Plastic Color: Black	
Display type:LCD displayControl elements:Master control, encodeControls:LimiterStatus LED:Power, signal, limitConnections:Output: line via 1 x 3-piInput channels:2 x mono with mic-line socket (XLR/jack), chailEqualizer:Master: 1 x 3-band toneSpeaker:1 x woofer 12" Voice coil lows 2,4" with Voice coil compressionType of speaker:Compact cabinet speakType of construction:VentedCarrying handle:3 pc/pcsMaterial:PlasticColor:Black	
Control elements: Master control, encode Controls: Limiter Status LED: Power, signal, limit Connections: Output: line via 1 x 3-pi Input channels: 2 x mono with mic-line socket (XLR/jack), char so	
Controls: Limiter Status LED: Power, signal, limit Connections: Output: line via 1 x 3-pi Input channels: 2 x mono with mic-line socket (XLR/jack), char Equalizer: Master: 1 x 3-band tone Speaker: 1 x woofer 12" Voice coil lows 2,4" with Voice coil compression Type of speaker: Compact cabinet speal Type of construction: Vented Carrying handle: 3 pc/pcs Material: Plastic Color: Black	
Status LED: Power, signal, limit Connections: Output: line via 1 x 3-pi Input channels: 2 x mono with mic-line socket (XLR/jack), charsed to be socket (X	er
Connections:Output: line via 1 x 3-piInput channels:2 x mono with mic-line socket (XLR/jack), charEqualizer:Master: 1 x 3-band toneSpeaker:1 x woofer 12" Voice coil lows 2,4" wit Voice coil compressionType of speaker:Compact cabinet speadType of construction:VentedCarrying handle:3 pc/pcsMaterial:PlasticColor:Black	
Input channels: 2 x mono with mic-line socket (XLR/jack), chan socket (XLR/jack)	
socket (XLR/jack), char Equalizer: Master: 1 x 3-band tone Speaker: 1 x woofer 12" Voice coil lows 2,4" with Voice coil compression Type of speaker: Compact cabinet speak Type of construction: Vented Carrying handle: 3 pc/pcs Material: Plastic Color: Black	in XLR
Speaker: 1 x woofer 12" Voice coil lows 2,4" wit Voice coil compression Type of speaker: Compact cabinet speak Type of construction: Vented Carrying handle: 3 pc/pcs Material: Plastic Color: Black	switch via Combination nnel control via rotary dial
Voice coil lows 2,4" with Voice coil compression Type of speaker: Compact cabinet speal Type of construction: Vented Carrying handle: 3 pc/pcs Material: Plastic Color: Black	e control
Type of construction:VentedCarrying handle:3 pc/pcsMaterial:PlasticColor:Black	-
Carrying handle:3 pc/pcsMaterial:PlasticColor:Black	ker
Material: Plastic Color: Black	
Color: Black	
Dimensions: Width: 38 cm	
Depth: 35 cm Height: 61 cm	
Weight: 15,45 kg	