

OMNITRONIC MAXX-1508 2-way Top 2x

2 x 8" passive full-range speaker, 150 W RMS

Art. No.: 11038833

GTIN: 4026397658064



The article is no longer in our assortment.

Description:

The MAXX-1508DSP is an active 2.1 PA system with 700 watts output power. It provides perfect sound and good level stability in various kinds of mobile PA applications.

The high-power 15" subwoofer with power-efficient Class D amplifier in a bass reflex cabinet delivers powerful, dry bass. The two satellite loudspeakers with 8" bass/midrange drivers and 1" compression drivers are equipped with a passive 2-way crossover including PTC tweeter protection and ensure a well-rounded sound experience.

Equipped with a DSP (digital signal processor) which enables convenient application presets for quick sound contouring, the MAXX-1508DSP offers combined XLR and 6.3 mm inputs with XLR parallel output (for linking additional systems), and an additional RCA input with level adjustment. Enjoy music wirelessly from your smartphone or any other Bluetooth device via the integrated Bluetooth audio receiver and charge them at the same time via the integrated powerbank.

The MAXX-1508DSP subwoofer's professional hardware includes a rugged multiplex/MDF enclosure, scratch-resistant lacquer, steel grille and ergonomically shaped handles. Swivel castors for easy transport are optionally available. Matching speaker stands, distance tubes, and stand forks are also available as accessories.

Features:

- 2-way bass-reflex system with 8" bass-midrange speaker and 1" compression driver
- Serve as a mobile 2.1 system together with the MAXX-1508 subwoofer
- With passive 2-way crossover, PTC tweeter protection
- Black metal grille with acoustic foam
- Application possibility: Standing; suspended; monitoring; on stand

Logistic

EAN / GTIN: 4026397658064

Weight: 18,35 kg

Length: 0.53 m

Width: 0.32 m

Height: 0.48 m

- With rigging points
- Rugged carrying handle
- For application areas such as: Mobile djs / entertainer; rental; mobile use

Package contents

- 2 x top, 2 x speaker cable

Technical specifications:

Power:	Program: 300W Rated: 150W RMS
Frequency range:	120 - 18000 Hz
Sensitivity:	92 dB
Max. SPL:	116 dB
Dispersion angle:	90° x 60°
Impedance:	4 ohms
Flying points:	5 x M8 thread
Connections:	Input: speaker via 1 x speaker built-in socket (F)
Speaker:	1 x woofer 8" 1 x compression tweeter highs 1"
Type of speaker:	Compact cabinet speaker
Carrying handle:	1 pc/pcs
Material:	MDF (medium density fiberboard), 16 mm
Dimensions:	Width: 25,5 cm Depth: 24,1 cm Height: 42,1 cm
Weight:	17,25 kg