

## OMNITRONIC MAXX-1810 2-way Top 2x

2 x 10" passive full-range speaker, 150 W RMS

Art. No.: 11038838

GTIN: 4026397663150



**List price: 391.51 €**

incl. 19% VAT.

### Description:

The MAXX-1810DSP is an active 2.1 PA system with 700 watts of continuous power (1400 watts peak) and 123 dB maximum SPL capability. It provides perfect sound and good level stability in various kinds of mobile PA applications.

The high-power 18" subwoofer with power-efficient Class D amplifier in a bass reflex cabinet delivers powerful, dry bass. The two satellite loudspeakers with 10" bass/midrange drivers and 1" compression drivers are equipped with a passive 2-way crossover including PTC tweeter protection and ensure a well-rounded sound experience.

Equipped with a DSP (digital signal processor) which enables convenient application presets for quick sound contouring, the MAXX-1810DSP offers combined XLR and 6.3 mm inputs with XLR parallel output (for linking additional systems), and an additional RCA input with level adjustment. Enjoy music wirelessly from your smartphone or any other Bluetooth device via the integrated Bluetooth audio receiver and charge them at the same time via the integrated powerbank.

The MAXX-1810DSP subwoofer's professional hardware includes a rugged multiplex/MDF enclosure, scratch-resistant lacquer, steel grille and ergonomically shaped handles. Swivel castors for easy transport are optionally available. Matching speaker stands, distance tubes, and stand forks are also available as accessories.

### Features:

- 2-way bass-reflex system with 10" bass-midrange speaker and 1" compression driver
- Serve as a mobile 2.1 system together with the MAXX-1810 subwoofer
- With passive 2-way crossover, PTC tweeter protection
- Black metal grille
- Rugged carrying handle

### Logistic

EAN / GTIN: 4026397663150

Weight: 21,25 kg

Length: 0.57 m

Width: 0.32 m

Height: 0.52 m

- With rigging points
- For application areas such as: Mobile use; mobile djs / entertainer; rental
- Application possibility: Suspended; monitoring; on stand; standing

**Package contents**

- 2 x top, 2 x speaker cable

**Technical specifications:**

Power:	Program: 300W Rated: 2x 150W RMS
Frequency range:	90 - 18000 Hz
Sensitivity:	93 dB
Max. SPL:	119 dB
Dispersion angle:	90° x 60°
Impedance:	4 ohms
Attachment system:	Flange: Ø 35mm
Flying points:	5 x M8 thread
Connections:	Input: speaker via 1 x speaker built-in socket (F)
Speaker:	1 x woofer 10" 1 x compression tweeter highs 1"
Type of speaker:	Compact cabinet speaker
Carrying handle:	1 pc/pcs
Dimensions:	Width: 28,5 cm Depth: 28,8 cm Height: 46,6 cm
Weight:	19,95 kg