

## OMNITRONIC AZX-212A 2-way Top active 250W

Active speaker with 12" woofer, 1,35" driver, 200 W RMS LF, 50 W RMS HF

### Art. No.: 11039029

GTIN: 4026397638844









# List price: 391.51 €

incl. 19% VAT.

#### Features:

- 2-way bass-reflex enclosure with 30 cm woofer and 3.5 cm titanium driver
- Balanced signal input XLR/6.3 mm jack, switchable mic/line
- HF adjustment -4 dB, -2 dB, 0 dB
- Black metal grille with acoustic foam
- Rugged carrying handle
- Application possibility: Standing; suspended; monitoring; on stand
- With rigging points
- Dual flange
- For application areas such as: Clubs/dancing school; installation; mobile use; mobile djs / entertainer; rental
- Package contents
- 1 x user manual, 1 x power cord, 1 x compact cabinet speaker

#### **Technical specifications:**

Power supply:	230 V AC, 50 Hz
Power consumption:	650 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power:	Rated: 200W RMS LF
	Rated: 50W RMS HF

#### Logistic

EAN / GTIN: 4026397638844 Weight: 20,60 kg Length: 0.43 m Width: 0.41 m Heigth: 0.68 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Frequency range:	55 - 20000 Hz
Sensitivity:	95 dB (1W/1m)
Attachment system:	Dual flange: Ø 35mm (0°/5°)
Flying points:	7 x M10 thread
Circuitry:	Class D Biamp
Control elements:	Power switch, Input sensitivity switch, tone control, level control
Controls:	Limiter
Status LED:	Limit, power, signal
Connections:	Input: 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version)
	Output: line via 1 x 3-pin XLR
Input channels:	1 x mono with mic-line switch via Combination socket (XLR/jack), channel control via rotary dial
Equalizer:	Master: 1 x 2-band tone control
Speaker:	Woofer 12" with ferrit magnet
	Basket material: steel
	Conematerial: cardboard/paper
	Voice coil lows 2"
	Voice coil compression tweeter highs 1,35"
Type of speaker:	Compact cabinet speaker
Carrying handle:	1 pc/pcs
Material:	MDF (medium density fiberboard), 15 mm
Color:	Black, textured coating, painted
Dimensions:	Width: 37 cm
	Depth: 35,2 cm
	Height: 62,2 cm
Weight:	19,15 kg