

CELTO ACOUSTIQUE iFIX6 G2 2-way Coaxial Speaker black

Art. No.: 11043561

Big sound in small package, mounting bracket included

GTIN:



List price: on demand €

incl. 19% VAT.

Features:

- Real 120 W power handling with high-end sound quality
- Coaxial transducer for unmatched spatial coherence
- Audiophile grade crossover with right phase topology
- Warm and deep full range system
- HF compression driver with ketone polymere dome
- Birch multiplex cabinet with tongue and groove assembly
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles; with mounting bracket
- CELTO ACOUSTIQUE driver
- Available in various colors
- For application areas such as: Theater; sports centres/gyms; clubs/dancing school; restaurants, bars and hotels

Logistic

Package contents

- 1 x top, 1 x mounting bracket, 2 x knurled screw, 1 x nut, 2 x washer, 1 x safety eyelet, 1 x screw plug-in terminal

Technical specifications:

Power:	Peak: 480W Program: 240W Rated: 120W AES
Frequency range:	65 - 22000 Hz
Sensitivity:	90 dB (1W/1m)

Max. SPL:	117 dB
Dispersion angle:	85° conical
Impedance:	12 ohms
Attachment system:	Panning and tilting mounting bracket for ceiling or wall installation in most varying angles Mounting bracket
Connections:	Input: speaker via screw plug-in terminal
Crossover frequency:	Passive 2500 Hz Recommended High-pass 30 Hz, 24db/oct in full-range mode High-pass 60-140 Hz with iFIX13S or iFIX17S subwoofer
Speaker:	1 x woofer 6" with ferrit magnet Basket material: aluminum Voice coil lows 1,5" 1 x compression tweeter highs 1" Voice coil compression tweeter highs 1" Diaphragmmaterial: Polymide
Type of speaker:	Coaxial speaker; on ceiling/on wall speaker
Type of construction:	Vented
Use of brands:	CELTO ACOUSTIQUE driver
Material:	Birch multiplex, 12 mm, CNC made with tongue and grove assembly
Color:	Black, textured coating, painted
Dimensions:	Width: 19 cm Depth: 25 cm Height: 26 cm
Weight:	5 kg