

CELTO ACOUSTIQUE iFIX10 G2 2-way Coaxial Speaker white

Big sound in small package, mounting bracket included

Art. No.: 11043571

GTIN:



List price: on demand €

incl. 19% VAT.

Features:

- Real 300 W power handling with high-end sound quality
- Coaxial transducer for unmatched spatial coherence
- High efficiency for incredible SPL to size ratio
- HF compression driver with ketone polymere dome
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles; with mounting bracket
- CELTO ACOUSTIQUE driver
- Available in various colors
- For application areas such as: Theater; sports centres/gyms; clubs/dancing school; restaurants, bars and hotels

Package contents

- 1 x top, 1 x mounting bracket, 1 x nut, 8 x washer, 1 x safety eyelet, 2 x screw, 1 x screw plug-in terminal

Logistic

Technical specifications:

Power:	Peak: 1200W Program: 600W Rated: 300W AES
Frequency range:	95 - 22000 Hz
Sensitivity:	97 dB (1W/1m)
Max. SPL:	128 dB

Dispersion angle:	80° conical
Impedance:	8 ohms
Attachment system:	Panning and tilting mounting bracket for ceiling or wall installation in most varying angles Mounting bracket
Connections:	Input: speaker via screw plug-in terminal
Crossover frequency:	Passive 1500 Hz Recommended In subwoofer combination High-pass 90-130 Hz, 24db/oct with iFIX13S or iFIX17S subwoofer
Speaker:	1 x woofer 10" with ferrit magnet Voice coil lows 2,5" Basket material: aluminum 1 x annular compression driver 1" Voice coil annular 1,75" Diaphragm material: PEEK (H.T. polymer)
Type of speaker:	On ceiling/on wall speaker; coaxial speaker
Type of construction:	Closed Box
Use of brands:	CELTO ACOUSTIQUE driver
Material:	Birch multiplex, 15 mm, CNC made with tongue and groove assembly
Color:	White, textured coating, painted
Dimensions:	Width: 30 cm Depth: 30,4 cm Height: 30 cm
Weight:	12 kg