

Dispersion angle:

Impedance:

Flying points:

CELTO ACOUSTIQUE CMP10 2-way Coaxial Speaker







List price: on demand €

incl. 19% VAT.

Features: Logistic With rigging points CELTO ACOUSTIQUE driver Built with NEUTRIK connector Rubberized Polyurea coating For application areas such as: Concerts/FoH's; clubs/dancing school; wedding/gala/events; Trade fair and shop fitting; installation; mobile use; stage; theater; rental; product presentations and lectures; trade fair construction Package contents 1 x top **Technical specifications:** Peak: 1200W Power: Program: 600W Rated: 300W AES 78 - 22000 Hz Frequency range: Sensitivity: 97 dB (1W/1m) Max. SPL: 128 dB

80° conical

8 ohms 7 x M8 thread

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Control elements:	Mode switch (1+1- / 2+2-)
Connections:	2 x 4-pol SpeakON mounting version (F)
Crossover frequency:	1500 Hz
Speaker:	1 x woofer 10" with ferrit magnet
	Basket material: aluminum
	Voice coil lows 2,5"
	1 x annular compression driver 1" with neodymium magnet
	Voice coil annular 1,75"
	Diaphragmmaterial: PEEK (H.T. polymer)
Type of speaker:	Coaxial speaker; compact cabinet speaker
Type of construction:	Vented
Use of brands:	CELTO ACOUSTIQUE driver
	Built with NEUTRIK connector
Material:	Birch multiplex
Color:	Black, rubberized Polyurea coating
Dimensions:	Width: 44 cm
	Depth: 29,8 cm
	Height: 30,6 cm
Weight:	15,00 kg