

CELTO ACOUSTIQUE CT12V 2-way Fullrange Loudspeaker

Perfectly built speaker

Art. No.: 11043672 GTIN:









List price: on demand €

incl. 19% VAT.

Features:

- Horn 90 degree rotatable for horizontal or vertical use

- With rigging points
- CELTO ACOUSTIQUE driver
- Built with NEUTRIK connector
- For application areas such as: Concerts/FoH's; clubs/dancing school; installation; mobile use; stage; theater; sports centres/gyms; multi-purpose hall
- Dual flange
- Package contents
- 1 x top

Technical specifications:

Power:	Peak: 2000W
	Program: 1000W
	Rated: 500W AES
Frequency range:	52 - 22000 Hz
Sensitivity:	97 dB (1W/1m)
Max. SPL:	130 dB
Dispersion angle:	80° x 50° rotatable horn
Impedance:	8 ohms
Attachment system:	Dual flange: Ø 35mm (0°/10°)

Logistic

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Flying points:	11 x M8 thread
Connections:	2 x 4-pol SpeakON mounting version (F)
Crossover frequency:	Passive 1600 Hz
Speaker:	1 x woofer 12"
	Basket material: aluminum
	Voice coil lows 3"
	1 x annular compression driver 1"
	Voice coil annular 1,75"
	Diaphragmmaterial: PEEK (H.T. polymer)
Type of speaker:	Compact cabinet speaker
Type of construction:	Vented
Use of brands:	CELTO ACOUSTIQUE driver
	Built with NEUTRIK connector
Material:	Birch multiplex
Color:	Black, textured coating, painted
Dimensions:	Width: 62 cm
	Depth: 34,5 cm
	Height: 35,6 cm
Weight:	20,60 kg