

CELTO ACOUSTIQUE SU218TL Transmission Line Subwoofer

Large-scale subwoofer, maximum SPL

Art. No.: 11043690

GTIN: 4026397664041



List price: on demand €

incl. 19% VAT.

Features:

- Rear-loaded transmission line subwoofer
- Down to 28Hz at -6dB and still 104dB/1W/1m efficiency
- Real 3000 W RMS power capacity
- Premium 18" LF drivers with massive ± 15 mm linear Xmax
- Triple-forced cooling system for low power compression
- Heavy braced cabinet for vibration free dynamic response
- For application areas such as: Theater; sports centres/gyms; clubs/dancing school
- CELTO ACOUSTIQUE driver
- Built with NEUTRIK connector
- Rubberized Polyurea coating

Package contents

- 1 x bass

Logistic

EAN / GTIN: 4026397664041

Weight: 124,65 kg

Length: 0.85 m

Width: 0.70 m

Height: 1.40 m

Bulky product

Technical specifications:

Power:	Peak: 12000W Program: 6000W Rated: 3000W AES
Frequency range:	26 - 900 Hz
Sensitivity:	104 dB (1W/1m)
Max. SPL:	145 dB
Dispersion angle:	Omnidirectional

Impedance:	4 ohms
Attachment system:	Flange: 2x M20 thread
Connections:	Input: speaker via 3 x 4-pol SpeakON mounting version (F)
Crossover frequency:	Recommended High-pass 28 Hz, 24db/oct Low-pass 80-110 Hz
Speaker:	2 x woofer 18" with ferrit magnet Basket material: aluminum Voice coil woofer in/out wound 4"
Type of speaker:	Subwoofer
Type of construction:	Transmission line
Use of brands:	CELTO ACOUSTIQUE driver Built with NEUTRIK connector
Material:	Baltic birch plywood, 18 mm, CNC made with tongue and groove assembly
Color:	Black, rubberized Polyurea coating, painted
Dimensions:	Width: 124,6 cm Depth: 72,8 cm Height: 58,0 cm
Weight:	111,00 kg