

**CELTO ACOUSTIQUE IWAC118S Subwoofer**

Subwoofer with integrated rigging system, lightweight design

Art. No.: 11043705

GTIN:



**List price: on demand €**

incl. 19% VAT.

**Features:**

- Real 1200 W RMS power capacity
- Premium 18" Neodymium driver with  $\pm 11$ mm linear Xmax
- Triple-forced cooling system for low power compression
- Heavy braced cabinet for vibration free dynamic response
- Fully integrated rigging & stacking system
- Touring-grade textured coating finish
- For application areas such as: Theater; concerts/FoH's; sports centres/gyms; stage; rental

**Logistic**

**Package contents**

- 1 x bass

**Technical specifications:**

Power:	Peak: 4800W Program: 2400W Rated: 1200W RMS
Frequency range:	33 - 100 Hz
Sensitivity:	97 dB (1W/1m)
Max. SPL:	133 dB
Dispersion angle:	Omnidirectional
Impedance:	4 ohms
Attachment system:	M20 thread

Flying points:	With integrate rigging system
Connections:	Speaker via 3 x 4-pol SpeakON mounting version (F)
Crossover frequency:	Active mode only Recommended High-pass 30 Hz, 24db/oct Low-pass 70-120 Hz when used with IWAC210
Speaker:	1 x tweeter 18" with neodymium magnet with dual demodulating rings Basket material: aluminum Voice coil woofer in/out wound 4"
Material:	Baltic birch plywood, 18 mm, CNC made with tongue and groove assembly
Color:	Black, matte
Dimensions:	Width: 70 cm Depth: 51,8 cm Height: 74,5 cm
Weight:	58,00 kg