

CELTO ACOUSTIQUE IR18S Subwoofer

IR18S: the right solution for a wide range of applications











List price: on demand €

incl. 19% VAT.

Features:

- Real 1200 W RMS power capacity
- Premium 18" Neodymium driver with ±11mm linear Xmax
- Triple-forced cooling system for low power compression
- Heavy braced cabinet for vibration free dynamic response
- Fully integrated rigging for floor stacking and flying
- Wheels optional
- Wheelboard optional
- Rubberized Polyurea coating
 Package contents
- 1 x bass

Technical specifications:

Power:	Peak: 4800W	
	Program: 2400W	
	Rated: 1200W RMS	
Frequency range:	33 - 120 Hz	
Sensitivity:	97 dB (1W/1m)	
Max. SPL:	134 dB	
Dispersion angle:	Omnidirectional	
Impedance:	8 ohms	

Logistic

EAN / GTIN: 4026397680980

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Attachment system:	1x M20 thread	
Flying points:	With integrate rigging system	
Control elements:	Mode switch (1+1- / 2+2-)	
Connections:	3 x 4-pol SpeakON mounting version (F)	
Crossover frequency:	Active mode only	
	Recommended	
	Low-pass 70-120 Hz	
Speaker:	1 x woofer 18" with neodymium magnet	
	Basket material: aluminum	
	Voice coil lows 4"	
Type of speaker:	Subwoofer	
Type of construction:	Vented	
Transport aid:	Wheels optional	
	Wheelboard optional	
Material:	Birch multiplex, CNC made with tongue and grove assembly	
Color:	Black, rubberized Polyurea coating	
Dimensions:	Width: 42 cm	
	Depth: 78 cm	
	Height: 58,5 cm	
Weight:	45,00 kg	