INTUSØNIC

INTUSONIC 4VM100T 2-way Fullrange Column Array Speaker white

Column array (4 x 4") with wave guide for multimedia applications, 280 W

Art. No.: 12604184 GTIN: 5060502923516







List price: on demand €

incl. 19% VAT.

Description:

The INTUCAB 4VM100T column array is a real full-range speaker specifically designed for multimedia applications. It offers precise dispersion with tight vertical control to avoid unwanted reflections from ceilings and floors, but wide horizontal coverage. Custom-designed waveguide and phase plug parts allow this speaker to perfectly address the medium-throw requirements of seated audiences in class rooms, lecture rooms, chapels and board rooms. Mounting options include flying, vesa brackets, and flush wall mounting. Available in black and white structural paint finish.

Features:

- Optimized for best possible speech reproduction
- For applications where multimedia capabilities, especially reproduction of music, the INTUSONIC 8SM300T is recommended as extension
- Advanced passive crossover for best sound quality
- With rigging points
- Scratchproof and shockproof
- White metal grille with acoustic foam
- For further information about this product, please refer to the Data Sheet under "Downloads"
- Package contents
- 1 x top, 1 x user manual, 1 x screw plug-in terminal, 4 x safety eyelet, 4 x foot, 4 x screw

Technical specifications:

IP classification:

IP20

Logistic

EAN / GTIN: 5060502923516 Weight: 10,50 kg Length: 1.06 m Width: 0.23 m Heigth: 0.21 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Program: 280W
90 - 18000 Hz
90 dB (1W/1m)
114 dB
120° x 30°
4 ohms
VESA standard
1 x M10 thread; 3 x M6 thread
Screw plug-in terminal
Speaker built-in socket (F)
Link: speaker built-in socket (F)
4 x woofer 4"
Conematerial: cardboard/paper with phase plug
4 x dome tweeter 1"
Silk with wave guide
On ceiling/on wall speaker; pendant speaker
MDF (medium density fiberboard), 12 mm
White, textured coating, scratchproof and shockproof
Width: 16 cm
Depth: 14 cm
Height: 100 cm
9,65 kg