

# **EUROLITE Set 2x LED CBB-4 + DMX LED Color Chief Controller**

2x LED light effect bar with RGB color mixing including DMX lighting desk

Art. No.: 20000432

GTIN:







**List price: 660.45 €** 

incl. 19% VAT.

Features: Logistic

#### **EUROLITE LED CBB-4 COB RGB Bar**

LED light effect bar with RGB color mixing, incl. IR remote control

- 4 powerful LEDs 23 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by low-noise cooling fan
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
- Flicker-free
- With a beam angle of 39°
- With mounting bracket
- 4 digit 7-segment LED display
- Preprogrammed in Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4;
   LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2;
   EASY SHOW 3; Colorchief
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; theater; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

#### Package contents

- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

# **EUROLITE DMX LED Color Chief Controller**

DMX lighting desk with innovative control concept for LED spotlights

- Easy control of LED spotlights with up to 6 colors, light bars as well as simple lighting effects
- For 8 devices or device groups, each with up to 4 segments
- Quick and easy programming
- Additional fixtures can be configured manually
- 8 color effects directly selectable
- 3 additional channels available per fixture (e.g. for rotations)
- Color wheel selection and simulation
- 24 memory spaces for scenes and chases
- Several chases and scenes can be run simultaneously
- USB port for storing program data
- Sound control via audio signal or TAP button
- Master dimming, fade time and run time easily adjustable
- Programmable 24 scenes/chases distributed over 1 page/s
- Can transmit up to 240 DMX channels
- Control via DMX; sound to light via RCA (F) mounting version; sound to light via microphone
- (19") 48.3 cm rack installation 3 U
- Desktop console housing
- For application areas such as: Clubs/dancing school; party room; Trade fair and shop fitting; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation
- Firmware can be updated

#### Package contents

- 1 x controller, 1 x user manual, 1 x external mains adapter

# **Technical specifications:**

Weight: 10,19 kg

### **EUROLITE LED CBB-4 COB RGB Bar**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	70 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	4 x 23 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
DMX channels:	3; 5; 12; 15; 19
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	1 x low-noise cooling fan
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
Preprogrammed in:	Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free

Beam angle (1/2 peak):  Beam angle (1/10 peak):  Housing color:  Black  Attachment system:  Mounting bracket  Display type:  4 digit 7-segment LED display  Dimensions:  Length: 46 cm Depth: 16 cm Height: 16 cm  Weight:  3,97 kg  Noise classification:  Class 2 (slight noise)  Mounting bracket  Diameter mounting holes:  3 x Ø11mm; 4 x Ø8mm  Material:  Metal, 2,5 mm  Power cord  Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Approx. 1,1 m  Remote control  Battery:  1 x button cell 3.0 V CR2025 lithium manganese built-in  Legal specifications  Special product:  Not designed for household room illumination  Intended use:  Show effect lighting	Beam angle:	39°
Housing color:  Attachment system:  Display type:  4 digit 7-segment LED display  Dimensions:  Length: 46 cm Depth: 16 cm Height: 16 cm  Weight:  3,97 kg  Noise classification:  Class 2 (slight noise)  Mounting bracket  Diameter mounting holes:  3 x Ø11mm; 4 x Ø8mm  Material:  Metal, 2,5 mm  Power cord  Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Approx. 1,1 m  Remote control  Battery:  1 x button cell 3.0 V CR2025 lithium manganese built-in  Legal specifications  Special product:  Not designed for household room illumination	Beam angle (1/2 peak):	39°
Attachment system:  Display type:  4 digit 7-segment LED display  Dimensions:  Length: 46 cm Depth: 16 cm Height: 16 cm Weight:  3,97 kg  Noise classification:  Class 2 (slight noise)  Mounting bracket  Diameter mounting holes:  3 x Ø11mm; 4 x Ø8mm  Material:  Metal, 2,5 mm  Power cord  Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Approx. 1,1 m  Remote control  Battery:  1 x button cell 3.0 V CR2025 lithium manganese built-in  Legal specifications  Special product:  Not designed for household room illumination	Beam angle (1/10 peak):	70°
Display type:  4 digit 7-segment LED display  Dimensions:  Length: 46 cm Depth: 16 cm Height: 16 cm Weight:  3,97 kg  Noise classification:  Class 2 (slight noise)  Mounting bracket  Diameter mounting holes:  3 x Ø11mm; 4 x Ø8mm  Material:  Metal, 2,5 mm  Power cord  Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Approx. 1,1 m  Remote control  Battery:  1 x button cell 3.0 V CR2025 lithium manganese built-in  Legal specifications  Special product:  Not designed for household room illumination	Housing color:	Black
Dimensions:  Length: 46 cm Depth: 16 cm Height: 16 cm  Weight:  3,97 kg  Noise classification:  Class 2 (slight noise)  Mounting bracket  Diameter mounting holes:  3 x Ø11mm; 4 x Ø8mm  Material:  Metal, 2,5 mm  Power cord  Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Approx. 1,1 m  Remote control  Battery:  1 x button cell 3.0 V CR2025 lithium manganese built-in  Legal specifications  Special product:  Not designed for household room illumination	Attachment system:	Mounting bracket
Depth: 16 cm Height: 16 cm  Weight: 3,97 kg  Noise classification: Class 2 (slight noise)  Mounting bracket  Diameter mounting holes: 3 x Ø11mm; 4 x Ø8mm  Material: Metal, 2,5 mm  Power cord  Cable construction: 3 x 0,75 mm² H05VV-F  Cable length: Approx. 1,1 m  Remote control  Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in  Legal specifications  Special product: Not designed for household room illumination	Display type:	4 digit 7-segment LED display
Noise classification:  Mounting bracket  Diameter mounting holes:  3 x Ø11mm; 4 x Ø8mm  Material:  Metal, 2,5 mm  Power cord  Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Approx. 1,1 m  Remote control  Battery:  1 x button cell 3.0 V CR2025 lithium manganese built-in  Legal specifications  Special product:  Not designed for household room illumination	Dimensions:	Depth: 16 cm
Mounting bracket  Diameter mounting holes: 3 x Ø11mm; 4 x Ø8mm  Material: Metal, 2,5 mm  Power cord  Cable construction: 3 x 0,75 mm² H05VV-F  Cable length: Approx. 1,1 m  Remote control  Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in  Legal specifications  Special product: Not designed for household room illumination	Weight:	3,97 kg
Diameter mounting holes:  3 x Ø11mm; 4 x Ø8mm  Metal, 2,5 mm  Power cord  Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Approx. 1,1 m  Remote control  Battery:  1 x button cell 3.0 V CR2025 lithium manganese built-in  Legal specifications  Special product:  Not designed for household room illumination	Noise classification:	Class 2 (slight noise)
Material:  Power cord  Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Approx. 1,1 m  Remote control  Battery:  1 x button cell 3.0 V CR2025 lithium manganese built-in  Legal specifications  Special product:  Not designed for household room illumination	Mounting bracket	
Power cord  Cable construction: 3 x 0,75 mm² H05VV-F  Cable length: Approx. 1,1 m  Remote control  Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in  Legal specifications  Special product: Not designed for household room illumination	Diameter mounting holes:	3 x Ø11mm; 4 x Ø8mm
Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Approx. 1,1 m  Remote control  Battery:  1 x button cell 3.0 V CR2025 lithium manganese built-in  Legal specifications  Special product:  Not designed for household room illumination	Material:	Metal, 2,5 mm
Cable length:  Remote control  Battery:  1 x button cell 3.0 V CR2025 lithium manganese built-in  Legal specifications  Special product:  Not designed for household room illumination	Power cord	
Remote control  Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in  Legal specifications  Special product: Not designed for household room illumination	Cable construction:	3 x 0,75 mm² H05VV-F
Battery:  1 x button cell 3.0 V CR2025 lithium manganese built-in  Legal specifications  Special product:  Not designed for household room illumination	Cable length:	Approx. 1,1 m
built-in  Legal specifications  Special product: Not designed for household room illumination	Remote control	
Special product: Not designed for household room illumination	Battery:	· · · · · · · · · · · · · · · · · · ·
	Legal specifications	
Intended use: Show effect lighting	Special product:	Not designed for household room illumination
	Intended use:	Show effect lighting

# **EUROLITE DMX LED Color Chief Controller**

Power supply:	100-240 V AC, 50/60 Hz
	9V DC 800 mA
Power consumption:	7,2 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Programs:	Programmable 24 scenes/chases distributed over 1 page/s
DMX channels:	Output 240
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; sound to light via RCA (F) mounting version; sound to light via microphone
Housing color:	Black
Available storage media:	USB devices (FAT 32)
USB port:	Туре А
Color:	Black
PC connect:	, firmware can be updated
Housing design:	(19") 48.3 cm rack installation 3 U
	Desktop console housing

Dimensions:

Width: 48,3 cm

Depth: 13,35 cm

Height: 8,5 cm

Weight:

2,25 kg

Noise classification:

Class 0 (no noise at all)