

EUROLITE Set 2x LED KLS-180 + 2x LED WF-40 + DMX LED Color Chief Controller

2x Compact Light Set, 2x Projection effect for water reflections including DMX lighting desk

0000435

GTIN:



List price: 1486.31 €

incl. 19% VAT.

Features:

EUROLITE LED KLS-180 Compact Light Set

Bar with 4 RGBW spots and 4 white strobe LEDs, with QuickDMX connector (XLR)

- Crossbar with integrated DMX control unit and stand sleeve
- Compact lightweight
- Silent operation
- Color blend stepless; color change adjustable; colors preset; Dimmer electronic
- Strobe effect
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function; QuickDMX via 5-pin XLR (M) mounting version (optional)
- Flicker-free
- With mounting bracket
- Mains input and output for power linking up to 8 units
- Preprogrammed in LED PC-Control 512; Light Captain; Light J; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
- For application areas such as: Party room; mobile use; mobile djs / entertainer; small rental
- Application possibility: On stand

spotlight

- 4 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
4 spots controlled separately

bar

- 4 powerful LEDs 1 W high-power cold white (CW)
 LEDs controlled separately

Package contents

- 1 x spotlight, 1 x bag, 1 x remote control, 1 x battery, 1 x power cord, 1 x user manual

Logistic

EUROLITE LED WF-40 Water Effect

Projection effect for water reflections, with RGBW color mixing & DMX

- Static and moving water effects with a 3D look in vibrant colors
 - 1 powerful LED 40 W COB (chip-on-board) 4in1 QCL RGBW
 - Focus manual
 - Beam effect; strobe effect
 - Integrated show programs
 - Direct color selection for 18 preset colors
 - The device is cooled by passive convection cooling
 - Control via DMX; sound to light via microphone; stand-alone; master/slave function
 - With mounting bracket
 - Dimmer electronic; color blend stepless; Rotation speed stepless; color change adjustable
 - Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; Colorchief
 - Monochrome 4 digit 7-segment LED display
 - For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels
 - Application possibility: Suspended; on stand
- Package contents**
- 1 x light effect, 1 x power cord, 1 x user manual

EUROLITE DMX LED Color Chief Controller

DMX lighting desk with innovative control concept for LED spotlights

- Easy control of LED spotlights with up to 6 colors, light bars as well as simple lighting effects
 - For 8 devices or device groups, each with up to 4 segments
 - Quick and easy programming
 - Additional fixtures can be configured manually
 - 8 color effects directly selectable
 - 3 additional channels available per fixture (e.g. for rotations)
 - Color wheel selection and simulation
 - 24 memory spaces for scenes and chases
 - Several chases and scenes can be run simultaneously
 - USB port for storing program data
 - Sound control via audio signal or TAP button
 - Master dimming, fade time and run time easily adjustable
 - Programmable 24 scenes/chases distributed over 1 page/s
 - Can transmit up to 240 DMX channels
 - Control via DMX; sound to light via RCA (F) mounting version; sound to light via microphone
 - (19") 48.3 cm rack installation 3 U
 - Desktop console housing
 - For application areas such as: Clubs/dancing school; party room; Trade fair and shop fitting; mobile djs / entertainer; restaurants, bars and hotels
 - Silent operation
 - Firmware can be updated
- Package contents**
- 1 x controller, 1 x user manual, 1 x external mains adapter

Technical specifications:

EUROLITE LED KLS-180 Compact Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	80 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version

Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
DMX channels:	3; 4; 8; 21
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function; QuickDMX via 5-pin XLR (M) mounting version (optional)
Preprogrammed in:	LED PC-Control 512; Light Captain; Light´J; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	9°
Beam angle (1/2 peak):	9°
Beam angle (1/10 peak):	18°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	Monochrome 4 digit 7-segment LED display
Dimensions:	Width: 60,5 cm Depth: 14 cm Height: 23 cm
Weight:	4,85 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Spotlight	
LED type:	4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Bar	
LED type:	4 x 1 W high-power cold white (CW)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE LED WF-40 Water Effect

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	25 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included

Device fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 40 W COB (chip-on-board) 4in1 QCL RGBW
Flash rate:	2,5 - 19 Hz
Equipment:	Focus manual
DMX channels:	9
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; sound to light via microphone; stand-alone; master/slave function
Preprogrammed in:	Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; Colorchief
Beam angle (1/2 peak):	30°
Housing color:	Black matte
Attachment system:	Mounting bracket
Display type:	Monochrome 4 digit 7-segment LED display
Material:	Metal
Dimensions:	Width: 27,7 cm Depth: 25,2 cm Height: 18,7 cm
Weight:	3,32 kg
Noise classification:	Class 2 (slight noise)
Power cord	
Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	Approx. 1,4 m
Mounting bracket	
Diameter mounting holes:	3 x Ø10mm
Material:	Metal, 2 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE DMX LED Color Chief Controller

Power supply:	100-240 V AC, 50/60 Hz 9V DC 800 mA
Power consumption:	7,2 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Programs:	Programmable 24 scenes/chases distributed over 1 page/s
DMX channels:	Output 240

DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; sound to light via RCA (F) mounting version; sound to light via microphone
Housing color:	Black
Available storage media:	USB devices (FAT 32)
USB port:	Type A
Color:	Black
PC connect:	, firmware can be updated
Housing design:	(19") 48.3 cm rack installation 3 U Desktop console housing
Dimensions:	Width: 48,3 cm Depth: 13,35 cm Height: 8,5 cm
Weight:	2,25 kg
Noise classification:	Class 0 (no noise at all)