

EUROLITE Set 4x AKKU IP Flat Light 1 chrome + Case + Charger

4x flat spotlight with 15 W RGBW LED, flightcase and charger

Art. No.: 20000443

GTIN:



List price: 1545.81 €

incl. 19% VAT.

Features:

EUROLITE AKKU IP Flat Light 1 cr

Flat IP65 spotlight in chrome with 1 x 15 W 4in1 QCL RGBW LED, QuickDMX transceiver

- Integrated QuickDMX transceiver for wireless DMX control
- Chrome housing
- Battery operation up to 18h depending on program used
- 1 powerful LED 15 W high-power 4in1 QCL RGBW (homogenous color mix)
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; QuickDMX; IR remote control; DMX
- Flicker-free
- With a beam angle of 8°
- With mounting bracket
- OLED display
- Suitable for outdoor use IP65
- For application areas such as: Small rental; wedding/gala/events; mobile djs / entertainer; video and photography
- Dimmer speed (step response) adjustable; Dimmer electronic; color blend stepless; color change adjustable; colors preset
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- Silent operation
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator
- Application possibility: Standing

Package contents

Logistic

- 1 x device, 1 x external mains adapter, 1 x remote control, 1 x battery, 1 x declaration of conformity, 1 x user manual

ROADINGER Flightcase 4x AKKU Flat Light Series

Carrying case, PRO version

- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- Rugged carrying handle
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

EUROLITE Charger 4x Akku Flat Light Series

Power supply with cable for simultaneous charging of 4 x AKKU Flat Light 1/3

- 1 x charger, 1 x power cord, 1 x adapter cable

Technical specifications:

Weight: 11,15 kg

EUROLITE AKKU IP Flat Light 1 cr

Power supply:	100-240 V AC, 50/60 Hz 12,6 V DC 2500 V
IP classification:	IP65
Protection class:	Protection class III
Power connection:	Battery/battery pack Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Battery pack type:	2 x lithium ion 11,1 V, 2600 mAh, 28,86 Wh
Battery pack:	Battery operation up to 18h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED type:	1 x 15 W high-power 4in1 QCL RGBW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 10
Cooling:	Passive convection cooling
Control:	Stand-alone; QuickDMX; IR remote control; DMX
Preprogrammed in:	Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Carrier frequency:	2,4 GHz

Beam angle:	8°
Beam angle (1/2 peak):	8°
Housing color:	Chrome
Attachment system:	Mounting bracket
Display type:	OLED display
Dimensions:	Width: 17,2 cm Depth: 13,8 cm Height: 6,4 cm
Weight:	1,63 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x AKKU Flat Light Series

Aluminum profile frames:	25 mm
Carrying handle:	1 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	8 cm x 19 cm x 10 cm
Accessory compartment:	38 cm x 6,5 cm x 12 cm
Inside dimensions:	38 cm x 27 cm x 12 cm
Dimensions:	Width: 42 cm Depth: 31 cm Height: 20 cm
Weight:	4,15 kg

EUROLITE Charger 4x Akku Flat Light Series

Power supply:	100-240 V AC, 50/60 Hz 12,6 V DC 6000 V
Power connection:	Mains input via C8 (M) "figure 8" mounting version power supply cord with Euro plug (provided)
Power output:	4 x coaxial power connector (F)
Weight:	0,49 kg