

EUROLITE Set 4x AKKU IP UP-4 QCL Spot QuickDMX + Case with charging function 0546

4x weather-proof Uplight with 4 x 10 W 4in1 LED including PRO flightcase with charging function

GTIN:



List price: 2259.81 €

incl. 19% VAT.

Features:

EUROLITE AKKU IP UP-4 QCL Spot QuickDMX

Weather-proof (IP65), uplight with 4 x 10 W 4in1 LED, QuickDMX & frost filter

- Integrated QuickDMX transceiver for wireless DMX control
- Additional frost filter provides a wide, soft and homogeneous light
- Battery operation up to 16h depending on program used
- 4 powerful LEDs 10 W high-power 4in1 QCL RGBW (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX; sound to light via microphone; IR remote control; master/slave function
- Flicker-free
- With a beam angle of 7°
- LCD display
- Suitable for outdoor use IP65
- With a KENSINGTON LOCK theft protection
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Dimmer speed (step response) adjustable; Dimmer electronic; color blend stepless; color change adjustable; colors preset
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator
- With bracket for floor use
- Preprogrammed in Light J; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
- Silent operation
- Application possibility: Standing

Logistic

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x frost filter, 1 x remote control, 1 x battery, 2 x knurled screw, 1 x mounting bracket, 2 x screw, 1 x declaration of conformity

ROADINGER Flightcase 4x AKKU IP UP-4 QuickDMX with charging function

Trunk case with castors

- With accessory compartment
- With 4 device compartments
- High-quality workmanship with plywood multi-layer glued 9 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- 4 castors with 2 locking brakes
- 4 built-in stacking trays in the cover

Package contents

- 1 x case, 1 x user manual, 1 x power cord

Technical specifications:

Weight: 33,21 kg

EUROLITE AKKU IP UP-4 QCL Spot QuickDMX

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Battery/battery pack Mains input via IP P-Con (Power in) yellow mounting version power supply cord with safety plug (provided)
Cable length:	Approx. 1,2 m
Battery pack type:	1 x lithium ion 14,8 V, 7800 mAh, 115,44 Wh
Battery pack:	Battery operation up to 16h depending on program used Recharging time 3h
Lamp type:	LED lamp
LED type:	4 x 10 W high-power 4in1 QCL RGBW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 10
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; QuickDMX; sound to light via microphone; IR remote control; master/slave function
Preprogrammed in:	Light J; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief

Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	7°
Beam angle (1/2 peak):	7°
Beam angle (1/10 peak):	20°
Housing color:	Black
Attachment system:	Bracket for floor use
Display type:	LCD display
Theft protection:	KENSINGTON LOCK
Dimensions:	Width: 15 cm Depth: 18 cm Height: 19,8 cm
Weight:	4,44 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x AKKU IP UP-4 QuickDMX with charging function

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	Max. 1150 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable length:	1,2 m
Device fuse:	5 x 20 mm, F 5 A fuse replaceable
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Material:	Plywood multi-layer glued, 9 mm
Color:	Black, laminated
Compartment dimensions:	18 cm x 15,5 cm x 14 cm
Accessory compartment:	7 cm x 43 cm x 14 cm
Inside dimensions:	56 cm x 43 cm x 20 cm
Dimensions:	Width: 60 cm Depth: 47 cm Height: 37,5 cm
Weight:	15,45 kg