

## EUROLITE Set 8x LED 7C-7 Silent Slim Spot + Case

8x inaudible 7in1 PAR spotlight in a space-saving design including PRO flightcase

Art. No.: 2000582

GTIN:



**List price: 2438.31 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED 7C-7 Silent Slim Spot

Silent 7in1 LED PAR spotlight in a space-saving design

- Flat version requires minimal space when mounting
- 7 powerful LEDs 9 W high-power 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)
- Strobe effect
- Integrated show programs
- Direct color selection for 27 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 15°
- Very high color rendering index (CRI)
- With double bracket
- 4 digit 7-segment LED display
- Color blend stepless; Dimmer electronic
- Silent operation
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; theater; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

#### Package contents

- 1 x light effect, 1 x power cord, 1 x remote control, 1 x user manual

### Logistic

## ROADINGER Flightcase 8x SLS Size M

Trunk case, PRO version

- Individually adjustable and removable dividers for universal use
- With 8 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

Weight: 36,65 kg

---

## EUROLITE LED 7C-7 Silent Slim Spot

|                         |  |
|-------------------------|--|
| Power supply:           | 100-240 V AC, 50/60 Hz   |
| Power consumption:      | 45 W   |
| IP classification:      | IP20   |
| Protection class:       | Protection class I   |
| Power connection:       | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug (provided)  |
| Power output:           | 1 x P-Con (gray), mounting version   |
| Fuse:                   | 5 x 20 mm, T 1 A fuse replaceable  |
| Lamp type:              | LED lamp   |
| LED type:               | 7 x 9 W high-power 7in1 SCL<br>RGB/CW/WW/A/UV (homogenous color mix)   |
| Flash rate:             | 0 - 20 Hz  |
| DMX channels:           | 3; 4-1; 4-2; 4-3; 4-4; 5; 6; 7; 9; 12  |
| DMX input:              | 1 x 3-pin XLR (M) mounting version   |
| DMX output:             | 1 x 3-pin XLR (F) mounting version   |
| Cooling:                | Passive convection cooling   |
| Control:                | Stand-alone; DMX; IR remote control; sound to<br>light via microphone; master/slave function;<br>QuickDMX via USB (optional); W-DMX by<br>wireless solution via USB (optional); CRMX by<br>LumenRadio via USB (optional) |
| Preprogrammed in:       | LED PC-Control 512; EASY SHOW 1; Light<br>Captain; EASY SHOW 2; EASY SHOW 3  |
| Projection:             | Flicker-free   |
| Beam angle:             | 15°  |
| Beam angle (1/2 peak):  | 15°  |
| Beam angle (1/10 peak): | 33°  |

|                              |   |
|------------------------------|---|
| Color rendering index (CRI): | 92 Ra   |
| Housing color:               | Black matte   |
| Attachment system:           | Double bracket  |
| Display type:                | 4 digit 7-segment LED display                           |
| USB port:                    | Type A  |
| Material:                    | Aluminum casting; metal                                 |
| Dimensions:                  | Width: 22 cm<br>Depth: 11 cm<br>Height: 25,5 cm         |
| Weight:                      | 2,60 kg   |
| Noise classification:        | Class 0 (no noise at all)                               |
| Photobiological safety:      | Risk Group 0  |
| Mounting bracket             |   |
| Diameter mounting holes:     | 1 x Ø11mm   |
| Material:                    | Metal, 2,5 mm   |
| Power cord                   |   |
| Cable construction:          | 3 x 1,0 mm <sup>2</sup> H05VV-F                         |
| Cable length:                | Approx. 1,2 m   |
| Remote control               |   |
| Battery:                     | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Legal specifications         |   |
| Special product:             | Not designed for household room illumination            |
| Intended use:                | Show effect lighting                                    |

#### **ROADINGER Flightcase 8x SLS Size M**

|                          |   |
|--------------------------|---|
| Maximum load:            | 50 kg   |
| Aluminum profile frames: | 30 mm   |
| Case handle:             | 2 pc/pcs  |
| Stop hinge:              | 2 pc/pcs  |
| Lock:                    | Butterfly lock: 1 pc/pcs                            |
| Use of brands:           | Branded hardware                                    |
| Material:                | Birch multiplex, 7 mm                               |
| Color:                   | Dark brown, laminated                               |
| Compartment dimensions:  | 11,5 cm x 24 cm x 34 cm                             |
| Inside dimensions:       | 46 cm x 48 cm x 34 cm                               |
| Dimensions:              | Width: 53,5 cm<br>Depth: 53,5 cm<br>Height: 44,5 cm |
| Weight:                  | 13,35 kg  |