

## EUROLITE Set 2x LED PLL-360 3200K Panel + Case

2x surface light with 360 warm white LEDs and DMX including PRO flightcase

Art. No.: 2000600

GTIN:



**List price: 1331.61 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED PLL-360 3200K Panel

Surface light with 360 warm white (WW)LEDs and DMX

- 360 powerful LEDs 0,5 W SMD 2835 warm white (WW)
- Energy-saving, durable and environmentally friendly
- Frost filter provides a soft, homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- Silent operation
- Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by passive convection cooling
- Control via quick select potentiometer for brightness; DMX; master/slave function
- Flicker-free
- With a beam angle of 120°
- Very high color rendering index (CRI)
- With mounting bracket
- LCD display
- Slim, rugged metal housing
- For application areas such as: Video and photography; stage; Trade fair and shop fitting; theater
- Preprogrammed in Light´J; Light Captain
- Various versions available
- Dimmable
- Mains input and output for power linking up to 8 units
- Rugged carrying handle
- Application possibility: Suspended; on stand

#### Package contents

### Logistic

- 1 x spotlight, 1 x user manual, 1 x power cord

### ROADINGER Flightcase 2x LED PLL-360

Trunk case, PRO version

- With accessory compartment
- With 2 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Technical specifications:

Weight: 23,00 kg

### EUROLITE LED PLL-360 3200K Panel

|                              |                                                                                                  |
|------------------------------|--------------------------------------------------------------------------------------------------|
| Power supply:                | 100-240 V AC, 50/60 Hz                                                                           |
| Power consumption:           | 130 W                                                                                            |
| IP classification:           | IP20                                                                                             |
| Power connection:            | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output:                | IEC connector (F) mounting version                                                               |
| Lamp type:                   | LED lamp                                                                                         |
| Lamp specification:          | Dimmable                                                                                         |
| LED type:                    | 360 x 0,5 W SMD 2835 warm white (WW)                                                             |
| DMX channels:                | 3                                                                                                |
| DMX input:                   | 1 x 3-pin XLR (M) mounting version                                                               |
| DMX output:                  | 1 x 3-pin XLR (F) mounting version                                                               |
| Cooling:                     | Passive convection cooling                                                                       |
| Control:                     | Quick select potentiometer for brightness; DMX; master/slave function                            |
| Preprogrammed in:            | Light J; Light Captain                                                                           |
| Projection:                  | Flicker-free                                                                                     |
| Beam angle:                  | 120°                                                                                             |
| Beam angle (1/2 peak):       | 120°                                                                                             |
| Color temperature:           | 3200K                                                                                            |
| Color rendering index (CRI): | 94 Ra                                                                                            |
| Illuminance in Lux (lx):     | Warm white (WW) 3m: 403 lx, 6m: 118 lx                                                           |
| Luminous flux:               | 9367 lm                                                                                          |
| Housing color:               | Black                                                                                            |

|                                  |                                               |
|----------------------------------|-----------------------------------------------|
| Attachment system:               | Mounting bracket                              |
| Display type:                    | LCD display                                   |
| Carrying handle:                 | 1 pc/pcs                                      |
| Dimensions:                      | Width: 57 cm<br>Depth: 12 cm<br>Height: 31 cm |
| Weight:                          | 6,10 kg                                       |
| Noise classification:            | Class 0 (no noise at all)                     |
| Energy efficiency class (A - G): | F                                             |
| EPREL-Nr:                        | 1056205                                       |

#### **ROADINGER Flightcase 2x LED PLL-360**

|                          |                                               |
|--------------------------|-----------------------------------------------|
| Maximum load:            | 50 kg                                         |
| Aluminum profile frames: | 25 mm                                         |
| Case handle:             | 2 pc/pcs                                      |
| Stop hinge:              | 2 pc/pcs                                      |
| Lock:                    | Butterfly lock: 2 pc/pcs                      |
| Use of brands:           | Branded hardware                              |
| Material:                | Birch multiplex, 7 mm; birch multiplex        |
| Color:                   | Dark brown, laminated                         |
| Accessory compartment:   | 61 cm x 10,5 cm x 26 cm                       |
| Device compartment:      | 57 cm x 8 cm x 26 cm                          |
| Inside dimensions:       | 61 cm x 26 cm                                 |
| Dimensions:              | Width: 65 cm<br>Depth: 37 cm<br>Height: 48 cm |
| Weight:                  | 10,80 kg                                      |