

## EUROLITE Set 2x LED BAR-12 UV Bar + Soft Bag

2x Light effect bar (1 m) with UV LEDs including soft bag

Art. No.: 2000661

GTIN: 4026397671001



**List price: 403.41 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED BAR-12 UV Bar

LED bar (100cm) with 12 x 1 watt ultra violet (UV) LED

- 12 powerful LEDs 1 W high-power ultra violet (UV)
- Dimmer electronic
- UV effect
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 14°
- With mounting bracket
- 4 digit 7-segment LED display
- Silent operation
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; party room; restaurants, bars and hotels
- Application possibility: Suspended; wall mounting

#### Package contents

- 1 x light effect, 1 x power cord, 2 x mounting bracket, 2 x knurled screw, 2 x washer, 1 x user manual

#### EUROLITE SB-12 Soft Bag

Practical black soft bag for LED bars (1 m length), adjustable divider

- Ideal for 1 or 2 LED bars with 1 meter length

### Logistic

EAN / GTIN: 4026397671001

Weight: 8,00 kg

Length: 1.10 m

Width: 0.50 m

Height: 0.20 m

- Made of easy-care nylon
- With divider
- With 2 device compartments
- High-quality workmanship with textile , black
- Interior with foam padding
- 2 carrying straps
- 1 shoulder strap

## Technical specifications:

---

Weight: 5,90 kg

---

### EUROLITE LED BAR-12 UV Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	25 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	12 x 1 W high-power ultra violet (UV)
DMX channels:	1; 2
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Projection:	Flicker-free
Beam angle:	14°
Beam angle (1/2 peak):	14°
Beam angle (1/10 peak):	24°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 100 cm Depth: 8,5 cm Height: 11,5 cm
Weight:	2,65 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 0,75 mm <sup>2</sup> H05VV-F
Cable length:	Approx. 1,1 m

---

**Mounting bracket**

---

Diameter mounting holes: 1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø7mm

---

Material: Metal, 2 mm

---

**Legal specifications**

---

Special product: Not designed for household room illumination

---

Intended use: Show effect lighting

---

**EUROLITE SB-12 Soft Bag**

Maximum load: 20 kg

---

Carrying strap: 2 pc/pcs

---

Transport aid: 1 x shoulder strap

---

Material: Textile

---

Color: Black

---

Dimensions: Width: 107 cm  
Depth: 17 cm  
Height: 18 cm

---

Weight: 0,60 kg

---