

## EUROLITE Set 4x Multiflood Pro IP SMD RGBW Strobe/Wash + Case

4x weather-proof 3in1 LED effect light with RGBW color mixing incl. PRO flightcase

Art. No.: 2000678

GTIN: 4026397360936



**List price: 5234.81 €**

incl. 19% VAT.

### Features:

#### EUROLITE Multiflood Pro IP SMD RGBW Strobe/Wash

Weather-proof (IP65) 3in1 LED effect light with RGBW color mixing

- 1320 powerful LEDs 0,4 W SMD 5050 4in1 QCL RGBW (homogenous color mix)<BR>6 segments controlled separately
- 36 integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX
- With mounting bracket; with omega bracket
- Monochrome LCD display
- Suitable for outdoor use IP65
- Dimmer curves adjustable; color blend stepless; Dimmer electronic
- Strobe effect; wash effect; Blinder effect
- Direct color selection for 16 preset colors
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- With pressure compensation membrane
- For application areas such as: Stage; rental; architecture
- Application possibility: Standing; suspended

#### Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 2 x omega bracket, 1 x XLR cable

### Logistic

EAN / GTIN: 4026397360936

#### ROADINGER Flightcase 4x Multiflood Pro

Trunk case with castors, PRO version

- With 4 device compartments
- High-quality workmanship with birch multiplex 9,8 mm, black, laminated
- Interior with foam padding
- Cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 4 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- Branded hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

Weight: 90,15 kg

---

### EUROLITE Multiflood Pro IP SMD RGBW Strobe/Wash

|                        |                                                                                                                                                  |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:          | 100-240 V AC, 50/60 Hz                                                                                                                           |
| Power consumption:     | 315 W                                                                                                                                            |
| IP classification:     | IP65                                                                                                                                             |
| Protection class:      | Protection class I                                                                                                                               |
| Lamp type:             | LED lamp                                                                                                                                         |
| LED type:              | 1320 x 0,4 W SMD 5050 4in1 QCL RGBW<br>(homogenous color mix)                                                                                    |
| Flash rate:            | 0 - 20 Hz                                                                                                                                        |
| DMX channels:          | 4; 5; 7; 13; 15; 31                                                                                                                              |
| DMX input:             | 3-pin XLR (M) mounting version IP                                                                                                                |
| DMX output:            | 3-pin XLR (F) mounting version IP                                                                                                                |
| Cooling:               | Cooling fan                                                                                                                                      |
| Control:               | Stand-alone; DMX                                                                                                                                 |
| Preprogrammed in:      | LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3 |
| Beam angle (1/2 peak): | 120°                                                                                                                                             |
| Attachment system:     | Mounting bracket<br>2x omega bracket                                                                                                             |
| Display type:          | Monochrome LCD display                                                                                                                           |
| Dimensions:            | Width: 49 cm<br>Depth: 16 cm<br>Height: 28,5 cm                                                                                                  |
| Weight:                | 13,70 kg                                                                                                                                         |
| Noise classification:  | Class 4 (loud noises)                                                                                                                            |
| Legal specifications   |                                                                                                                                                  |
| Special product:       | Not designed for household room illumination                                                                                                     |
| Intended use:          | Show effect lighting                                                                                                                             |

**ROADINGER Flightcase 4x Multiflood Pro**

|                          |                                                |
|--------------------------|------------------------------------------------|
| Maximum load:            | 100 kg                                         |
| Aluminum profile frames: | 30 mm                                          |
| Case handle:             | 4 pc/pcs                                       |
| Stop hinge:              | 4 pc/pcs                                       |
| Lock:                    | Butterfly lock: 2 pc/pcs                       |
| Transport aid:           | 4 x castors with 2 locking brakes              |
| Use of brands:           | Branded hardware                               |
| Material:                | Birch multiplex, 9,8 mm; birch multiplex       |
| Color:                   | Black, laminated; dark brown, laminated        |
| Device compartment:      | 21,5 cm x 55,5 cm x 28 cm                      |
| Accessory compartment:   | 11,5 cm x 53,5 cm x 28 cm                      |
| Inside dimensions:       | 105,5 cm x 56 cm x 37 cm                       |
| Dimensions:              | Width: 110 cm<br>Depth: 61 cm<br>Height: 53 cm |
| Weight:                  | 35,35 kg                                       |