

# **EUROLITE Set 2x LED TMH-S200 + Case**

2x LED moving head spot including PRO flightcase

Art. No.: 20000737 GTIN: 4026397681512







List price: 2854.81 €

incl. 19% VAT.

#### Features:

2x LED moving head spot including PRO flightcase

- Positioning within TILT

#### **EUROLITE LED TMH-S200 Moving Head Spot**

LED moving head spot with color wheel, static & rot. gobo wheel, prism, frost, focus and zoom

- 1 powerful LED 200 W COB (chip-on-board) cold white (CW)
- Positioning within 540° PAN, 270° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Prism 3-fold rotating; frost filter; gobo wheel with rotating gobos; gobo wheel with static gobos; zoom motor driven; focus motor-driven; color wheel
- Color wheel with 9 dichroic filters plus open<BR>half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 9 gobos and open<BR>shake effect
- Gobo wheel with rotating gobos, 7 gobos and open<BR>shake effect
- Slot-in gobo system for easy gobo replacement
- Gobos changeable
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free

## Logistic

EAN / GTIN: 4026397681512

Weight: 60,00 kg Length: 1.20 m Width: 0.80 m Heigth: 0.72 m Bulky product

- With a beam angle of 8° 22°
- Multicolor LCD display
- Dimmer electronic; Dimmer speed (step response) adjustable
- Preprogrammed in Light Captain
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; rental
- Application possibility: Standing; suspended

#### Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 2 x omega bracket

## ROADINGER Flightcase 2x TMH-S200 with wheels

Trunk case with castors

- For optimal security
- With 2 device compartments
- High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding<BR>cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes

## **Technical specifications:**

Weight: 48,10 kg

## **EUROLITE LED TMH-S200 Moving Head Spot**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	250 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Device fuse:	5 x 20 mm, T 3,15 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 200 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	270° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	1 - 18 Hz
Equipment:	Prism 3-fold rotating; frost filter; gobo wheel with rotating gobos; gobo wheel with static gobos; zoom motor driven; focus motor-driven; color wheel
Color generation:	Color wheel with 9 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 9 gobos and open Shake effect

	Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 19,5mm Image diameter 15mm Shake effect Slot-in gobo system for easy gobo replacement
DMV skereste	Gobos changeable
DMX channels:	17
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light Captain
Projection:	Flicker-free
Beam angle:	8° - 22°
Beam angle (1/2 peak):	8 - 22°
Beam angle (1/10 peak):	8 - 22°
Illuminance in Lux (lx):	Narrow cold white (CW) 3m: 22622 lx, 6m: 6278 lx
	Wide cold white (CW) 1m: 31619 lx, 3m: 4309 lx, 6m: 1112 lx
Housing color:	Black
Display type:	Multicolor LCD display
Dimensions:	Width: 30,5 cm Depth: 33,0 cm Height: 51,5 cm
Weight:	14,70 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

## ROADINGER Flightcase 2x TMH-S200 with wheels

50 kg
30 mm
2 pc/pcs
2 pc/pcs
Butterfly lock: 2 pc/pcs
4 x castors with 2 locking brakes
Plywood multi-layer glued, 7 mm
Black, laminated
25,5 cm x 32 cm x 50 cm
63 cm x 32 cm x 50 cm

Accessory compartment:	6,5 cm x 32 cm x 19 cm
Dimensions:	Width: 67,5 cm
	Depth: 37 cm
	Height: 70,5 cm
Weight:	18,70 kg