

EUROLITE Set LED SL-400 DMX + STV-250

Follow spot with 300 W warm white LED including follow stand

Art. No.: 2000750

GTIN: 4026397682441



List price: 2616.81 €

incl. 19% VAT.

Features:

EUROLITE LED SL-400 DMX Search Light

Follow spot with warm white 300 W LED for medium distances, zoom, CRI >80

- Manual control via control panel with buttons and faders
- 1 powerful LED 300 W COB (chip-on-board) warm white (WW)
- Focus manual; iris stepless
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX
- With a beam angle of 7° - 17°
- Good color rendering index (CRI)
- With mounting bracket
- 4 digit 7-segment LED display
- Direct color temperature selection for 4 preset values
- Dimmer electronic
- Strobe effect
- Suitable for a range of use from 25 to 50 meters
- Color wheel with 5 dichroic filters plus open
half colors selectable
- Preprogrammed in LED PC-Control 512; Light Captain
- Built with SEETRONIC connector
- For application areas such as: Wedding/gala/events; stage; theater; rental
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x XLR cable, 1 x mounting bracket, 1 x hex key

Logistic

EAN / GTIN: 4026397682441

Weight: 24,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

EUROLITE STV-250 Follow Spot Stand, black

PRO follow stand for mobile lighting systems

- Heavy-duty stainless steel version for extra stability and safety
- Tripod legs made of stainless steel
- Tripod legs with optional slant for uneven surfaces
- Easy handling
- Safety ring for height adjustment
- Extra-big, rubberized star knob screw
- Adjustable height
- With Multi-angle ball head bracket with stainless steel rod

Package contents

- 1 x stand, 1 x user manual

Technical specifications:

Weight: 20,80 kg

EUROLITE LED SL-400 DMX Search Light

| | |
|------------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 440 W |
| IP classification: | IP20 |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Lamp type: | LED lamp |
| LED type: | 1 x 300 W COB (chip-on-board) warm white (WW) |
| Flash rate: | 1 - 20 Hz |
| Equipment: | Focus manual; iris stepless |
| Color generation: | Color wheel with 5 dichroic filters plus open Half colors selectable |
| DMX channels: | 6 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Temperature-controlled fan |
| Control: | Stand-alone; DMX |
| Preprogrammed in: | LED PC-Control 512; Light Captain |
| Beam angle: | 7° - 17° |
| Beam angle (1/2 peak): | 7 - 13° |
| Beam angle (1/10 peak): | 3 - 17° |
| Color temperature: | 3500K |
| Color rendering index (CRI): | 80 Ra |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Display type: | 4 digit 7-segment LED display |
| Use of brands: | Built with SEETRONIC connector |
| Range of use: | 25m - 50m |
| Dimensions: | Length: 77 cm Width: 27 cm |

| | |
|-----------------------|--|
| | Height: 29 cm |
| Weight: | 12,35 kg |
| Noise classification: | Class 2 (slight noise) |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

EUROLITE STV-250 Follow Spot Stand, black

| | |
|----------------------------|--|
| Maximum carrying capacity: | 50 kg |
| Height: | Maximum: 170 cm Minimum: 95 cm |
| Attachment system: | M10 thread Multi-angle ball head bracket with stainless steel rod |
| Type (general stands): | Light stand/manual |
| Material: | Aluminum; stainless steel |
| Color: | Black |
| Base area: | Ø 1,12 cm |
| Transport dimensions: | 13 cm x 14 cm x 105 cm |
| Weight: | 8,45 kg |