

EUROLITE Set AKKU THA-20PC TRC + Stand + Bag

Battery powered LED theater spot incl. speaker stand and matching transport bag

Art. No.: 20000796 GTIN: 4026397687392



List price: 315.35 €

incl. 19% VAT.

Features:

EUROLITE AKKU THA-20PC TRC Theater Spot bk

Battery powered LED theater spotlight with manual brightness regulation

- Two additional frost filters provide a soft, homogeneous light
- New LED technology that simulates the color temperature curve of a halogen lamp when dimming
- Rugged metal housing
- Battery operation up to 2h
- 1 powerful LED 17 W COB (chip-on-board) Dim to warm (homogenous color mix)
- Dimmer electronic
- The device is cooled by passive convection cooling
- Control via stand-alone
- Flicker-free
- With a beam angle of 17°
- Very high color rendering index (CRI)
- With mounting bracket
- Silent operation
- For application areas such as: Trade fair and shop fitting; wedding/gala/events; video and photography; restaurants, bars and hotels
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator
- Rubber feet
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x external mains adapter, 1 x filter frame, 1 x barndoor, 2 x frost filter

Logistic

EAN / GTIN: 4026397687392

Weight: 6,00 kg Length: 1.20 m Width: 0.60 m Heigth: 0.60 m

OMNITRONIC Speaker Stand BOB System

Speaker stand for BOB speakers, extendable up to 170 cm

- Tube diameter: Ø 30 mm
- Adjustable height
- Scratchproof and shockproof

Package contents

- 1 x stand, 1 x user manual

OMNITRONIC BOB Transport Bag for Tripod/Distance Tube

Accessory for the BOB series

- Suitable for stands and distance tubes
- Made of easy-care artificial black textile
- High-quality workmanship with textile , black

Package contents

- 1 x bag

Technical specifications:

Weight: 4,75 kg

EUROLITE AKKU THA-20PC TRC Theater Spot bk

| Power supply: | 100-240 V AC, 50/60 Hz |
|------------------------------|---|
| IP classification: | IP20 |
| Power connection: | Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided) |
| Battery pack type: | 1 x lithium ion 11,1 V, 2600 mAh, 28,86 Wh |
| Battery pack: | Battery operation up to 2h |
| | Recharging time 3h |
| LED type: | 1 x 17 W COB (chip-on-board) Dim to warm (homogenous color mix) |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone |
| Projection: | Flicker-free |
| Beam angle: | 17° |
| Beam angle (1/2 peak): | 17° |
| | Frost filter 19° |
| | Frost filter 26° |
| Color temperature: | 3000K |
| Color rendering index (CRI): | 92 Ra |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Transport aid: | Rubber feet |
| Dimensions: | Length: 21 cm |
| | Width: 14,5 cm |
| | Height: 21 cm |

| Weight: | 2,38 kg |
|-----------------------|--|
| Noise classification: | Class 0 (no noise at all) |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

OMNITRONIC Speaker Stand BOB System

| Maximum carrying capacity: | 14 kg |
|----------------------------|---|
| Height: | Maximum: 195 cm |
| | Minimum: 107 cm |
| | Adjustable in 6 steps with locking pin |
| Attachment system: | M10 thread |
| Type (general stands): | Speaker stand/manual |
| Material: | Steel |
| Color: | Black, painted; , scratchproof and shockproof |
| Main pipe diameter: | Ø 3 cm |
| Extension tube diameter: | Ø 2,5 cm |
| Weight: | 2,15 kg |
| | |

Locking screw M10 for STW

Weight: 0,03 kg

OMNITRONIC BOB Transport Bag for Tripod/Distance Tube

| Material: | Textile | |
|-------------|---------------|--|
| Color: | Black | |
| Dimensions: | Width: 106 cm | |
| | Depth: 9 cm | |
| | Height: 7 cm | |
| Weight: | 0,19 kg | |