

## EUROLITE Set AKKU THA-20PC TRC + Stand + Bag

Battery powered LED theater spot incl. speaker stand and matching transport bag

Art. No.: 20000796

GTIN: 4026397687392



**List price: 315.35 €**

incl. 19% VAT.

### Features:

#### EUROLITE AKKU THA-20PC TRC Theater Spot bk

Battery powered LED theater spotlight with manual brightness regulation

- Two additional frost filters provide a soft, homogeneous light
- New LED technology that simulates the color temperature curve of a halogen lamp when dimming
- Rugged metal housing
- Battery operation up to 2h
- 1 powerful LED 17 W COB (chip-on-board) Dim to warm (homogenous color mix)
- Dimmer electronic
- The device is cooled by passive convection cooling
- Control via stand-alone
- Flicker-free
- With a beam angle of 17°
- Very high color rendering index (CRI)
- With mounting bracket
- Silent operation
- For application areas such as: Trade fair and shop fitting; wedding/gala/events; video and photography; restaurants, bars and hotels
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator
- Rubber feet
- Application possibility: Suspended; on stand

#### Package contents

- 1 x spotlight, 1 x user manual, 1 x external mains adapter, 1 x filter frame, 1 x barndoor, 2 x frost filter

### Logistic

EAN / GTIN: 4026397687392

Weight: 6,00 kg

Length: 1.20 m

Width: 0.60 m

Height: 0.60 m

### OMNITRONIC Speaker Stand BOB System

Speaker stand for BOB speakers, extendable up to 170 cm

- Tube diameter: Ø 30 mm
- Adjustable height
- Scratchproof and shockproof

#### Package contents

- 1 x stand, 1 x user manual

### OMNITRONIC BOB Transport Bag for Tripod/Distance Tube

Accessory for the BOB series

- Suitable for stands and distance tubes
- Made of easy-care artificial black textile
- High-quality workmanship with textile, black

#### Package contents

- 1 x bag

### Technical specifications:

---

Weight: 4,75 kg

---

### EUROLITE AKKU THA-20PC TRC Theater Spot bk

Power supply: 100-240 V AC, 50/60 Hz

---

IP classification: IP20

---

Power connection: Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)

---

Battery pack type: 1 x lithium ion 11,1 V, 2600 mAh, 28,86 Wh

---

Battery pack: Battery operation up to 2h  
Recharging time 3h

---

LED type: 1 x 17 W COB (chip-on-board) Dim to warm (homogenous color mix)

---

Cooling: Passive convection cooling

---

Control: Stand-alone

---

Projection: Flicker-free

---

Beam angle: 17°

---

Beam angle (1/2 peak): 17°  
Frost filter 19°  
Frost filter 26°

---

Color temperature: 3000K

---

Color rendering index (CRI): 92 Ra

---

Housing color: Black

---

Attachment system: Mounting bracket

---

Transport aid: Rubber feet

---

Dimensions: Length: 21 cm  
Width: 14,5 cm  
Height: 21 cm

---

Weight:	2,38 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **OMNITRONIC Speaker Stand BOB System**

Maximum carrying capacity:	14 kg
Height:	Maximum: 195 cm Minimum: 107 cm Adjustable in 6 steps with locking pin
Attachment system:	M10 thread
Type (general stands):	Speaker stand/manual
Material:	Steel
Color:	Black, painted; , scratchproof and shockproof
Main pipe diameter:	Ø 3 cm
Extension tube diameter:	Ø 2,5 cm
Weight:	2,15 kg

#### **Locking screw M10 for STW**

Weight:	0,03 kg
---------	---------

#### **OMNITRONIC BOB Transport Bag for Tripod/Distance Tube**

Material:	Textile
Color:	Black
Dimensions:	Width: 106 cm Depth: 9 cm Height: 7 cm
Weight:	0,19 kg