



List price: 808.01 €

incl. 19% VAT.

Features:

EUROLITE LED KLS-3002 Next Compact Light Set

Bar with 4 powerful RGBAW/UV spots, QuickDMX support, IR remote control and carrying bag

- Crossbar with integrated DMX control unit and TV spigot for tripod installation
- 7 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix) spots controlled separately
- With a beam angle of 19°
- 20 integrated show programs
- Direct color selection for 21 preset colors
- Dimmer electronic; color blend stepless; color selection; program selection
- UV effect
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRM by LumenRadio via USB (optional)
- Preprogrammed in EASY SHOW 1; Light J; LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- For application areas such as: Mobile use; stage; mobile djs / entertainer; rental
- Mounting points and power outlets for additional fixtures
- Mains input and output for power linking up to 8 units
- Silent operation
- Application possibility: Suspended; on stand

Package contents

- 1 x device, 1 x user manual, 1 x declaration of conformity, 1 x power cord, 1 x remote control, 1 x bag, 2 x omega bracket, 4 x knurled screw, 4 x washer, 1 x battery, 1 x terminating plug (power)

Logistic

EAN / GTIN: 4026397689105

Weight: 20,00 kg

Length: 1.35 m

Width: 0.21 m

Height: 0.58 m

Bulky product

OMNITRONIC M-4 Speaker-System Stand

Aluminum speaker stand, height adjustable 140-345 cm, maximum load 18 kg

- Durable aluminum version
- Tube diameter: Ø 35 mm
- Adjustable height

Package contents

- 1 x user manual

EUROLITE STV-3529 Adapter long

Massive adapter for 35 mm tube, 28 mm TV spigot, maximum load WLL 100 kg

- For stands with telescopic tube 35 mm
- Connection element for cross beam with 28 mm TV spigot
- With M6 and M8 fixation screw
- Heavy version for highest stability
- TV spigot

Package contents

- 1 x device, 1 x user manual, 2 x knurled screw

Technical specifications:

Weight: 15,94 kg

EUROLITE LED KLS-3002 Next Compact Light Set

| | |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 225 W |
| IP classification: | IP20 |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Cable length: | 3 m |
| Power output: | 2 x IEC connector (F) mounting version fused 1 x P-Con (gray), mounting version Bypass |
| Device fuse: | 5 x 20 mm, T 2,5 A fuse replaceable |
| Power output fuse per channel: | 5 x 20 mm, T 5 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 7 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix) |
| DMX channels: | 2; 4; 6; 10; 24; 28 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |

| | |
|-------------------------|-------------------------------------------------------------------------------------------------------------------|
| Preprogrammed in: | EASY SHOW 1; Light J; LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3 |
| Beam angle: | 19° |
| Beam angle (1/2 peak): | 19° |
| Beam angle (1/10 peak): | 35° |
| Housing color: | Black |
| Attachment system: | TV spigot Ø 28mm Omega bracket |
| Dimensions: | Width: 128 cm Depth: 8 cm Height: 29 cm |
| Weight: | 11,14 kg |
| Noise classification: | Class 0 (no noise at all) |
| Remote control | |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

OMNITRONIC M-4 Speaker-System Stand

| | |
|----------------------------|-------------------------------------------------------------------------------|
| Maximum carrying capacity: | 18 kg |
| Tube diameter sector: | 38 - 35 mm |
| Height: | Maximum: 345 cm Minimum: 140 cm Adjustable in 10 steps with locking pin |
| Attachment system: | Ø 35mm |
| Type (general stands): | Speaker stand/manual |
| Material: | Aluminum |
| Color: | Black |
| Transport dimensions: | 140 cm x 13,5 cm |
| Weight: | 3,30 kg |

EUROLITE STV-3529 Adapter long

| | |
|-------------------------------|---------------------------------------------------|
| Maximum load BGV C1 (8-fold): | 50 kg |
| Maximum load WLL (4-fold): | 100 kg |
| Attachment system: | TV spigot Ø 28mm Ø 35mm |
| Type (general stands): | Accessory |
| Material: | Steel, 6 mm, powder-coated |
| Dimensions: | Width: 8,50 cm Depth: 5 cm Height: 19,50 cm |
| Weight: | 1,50 kg |