



List price: 1367.31 €

incl. 19% VAT.

Features:

- Positioning within TILT
 - <p>EUROLITE LED KLS Scan Next FX Compact Light Set
 - <p class="featureSatz">Compact bar with derby, spots, scanners, UV effect, QuickDMX port and bag
 - Crossbar with integrated DMX control unit and TV spigot for tripod installation
 - When fog is used, this effect becomes especially attractive
 - Positioning within TILT
 - Color wheel; gobo wheel with static gobos
 - 20 integrated show programs
 - Control via DMX; IR remote control; sound to light via microphone; stand-alone; master/slave function; wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - OLED display
 - For application areas such as: Rental; small rental; wedding/gala/events; mobile use; mobile djs / entertainer
 - Mains input and output for power linking up to 8 units
 - Color wheel with 8 dichroic filters plus open
half colors selectable
 - Preprogrammed in Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
 - Application possibility: Suspended; on stand
- spotlight**
- 3 powerful LEDs 7 W high-power 4in1 QCL RGB/WW (homogenous color mix)
4 spots controlled separately
 - With a beam angle of 15°
- light effect**
- 2 powerful LEDs 3 W R/G/B
- moving light**

Logistic

EAN / GTIN: 4026397690859

Weight: 23,22 kg

Length: 1.20 m

Width: 0.80 m

Height: 1.35 m

Bulky product

- 1 powerful LED 15 W cold white (CW)

bar

- 4 powerful LEDs 1 W high-power ultra violet (UV)
 LEDs controlled separately

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x declaration of conformity, 2 x mounting bracket, 1 x remote control, 1 x battery, 1 x bag, 2 x knurled screw, 2 x washer, 1 x terminating plug (power)
- <p>EUROLITE QuickDMX USB Wireless Transmitter/Receiver
- <p class="featureSatz">Wireless miniature DMX transceiver 2.4 GHz, phantom powered
- User-friendly USB plug with swivel antenna
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transceiver and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- LED indication for functions
- Transceiver, to be used as transmitter or receiver
- Requires 5 V phantom power for operation
- Can receive and process up to 512 DMX channels
- Can transmit up to 512 DMX channels
- Control via DMX; QuickDMX; plug and play
- Operating range up to 400m with line-of-sight
- Up to 6 transmitters can be operated in parallel without interference

Package contents

- 1 x device, 1 x user manual, 1 x declaration of conformity
- <p>EUROLITE QuickDMX Wireless Transmitter
- <p class="featureSatz">Compact wireless DMX transmitter 2.4 GHz
- User-friendly 3-pin XLR adapter (male) with swivel antenna
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transceiver and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- 1 to 512 QuickDMX receivers can be controlled by each transmitter
- LED indication for functions
- Transceiver, to be used as transmitter or receiver
- Can transmit up to 512 DMX channels
- Control via QuickDMX; DMX; plug and play
- Operating range up to 400m
- Up to 6 transmitters can be operated in parallel without interference

Package contents

- 1 x device, 1 x user manual, 1 x declaration of conformity, 1 x external mains adapter, 1 x USB cable
- <p>EUROLITE DMX LED Color Chief Controller
- <p class="featureSatz">DMX lighting desk with innovative control concept for LED spotlights
- Easy control of LED spotlights with up to 6 colors, light bars as well as simple lighting effects
- For 8 devices or device groups, each with up to 4 segments
- Quick and easy programming
- Additional fixtures can be configured manually
- 8 color effects directly selectable
- 3 additional channels available per fixture (e.g. for rotations)
- Color wheel selection and simulation
- 24 memory spaces for scenes and chases
- Several chases and scenes can be run simultaneously
- USB port for storing program data
- Sound control via audio signal or TAP button
- Master dimming, fade time and run time easily adjustable
- Programmable 24 scenes/chases distributed over 1 page/s
- Can transmit up to 240 DMX channels
- Control via DMX; sound to light via RCA (F) mounting version; sound to light via microphone
- (19") 48.3 cm rack installation 3 U
- Desktop console housing
- For application areas such as: Clubs/dancing school; party room; Trade fair and shop fitting; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation
- Firmware can be updated
- **Package contents**
- 1 x controller, 1 x user manual, 1 x external mains adapter

- <p>EUROLITE STV-60-WOT EU Steel Stand black
- <p class="featureSatz">Lighting stand, made in EU, maximum load 30 kg, height 150-315 cm
- Stable lighting stand for mobile use
- TV spigot
- Available in various colors
- Made in Europe
- For application areas such as: Mobile use
- Adjustable height
- Package contents**
- 1 x stand, 1 x user manual

Technical specifications:

Weight: 20,86 kg

EUROLITE LED KLS Scan Next FX Compact Light Set

| | |
|--------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 115 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | P-Con (gray), mounting version |
| Fuse: | 5 x 20 mm, T 2 A fuse replaceable |
| Lamp type: | LED lamp |
| Equipment: | Color wheel; gobo wheel with static gobos |
| Color generation: | Cold white (CW) |
| Color generation: | Color wheel with 8 dichroic filters plus open Half colors selectable |
| DMX channels: | 3; 7; 13; 14; 15; 18; 19; 30; 32; 39 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | DMX; IR remote control; sound to light via microphone; stand-alone; master/slave function; wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in: | Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief |
| Housing color: | Black |
| Attachment system: | TV spigot Ø 28mm 2x mounting bracket |
| Display type: | OLED display |
| Dimensions: | Width: 110 cm Depth: 15,5 cm Height: 43 cm |

| | |
|--------------------------|--|
| Weight: | 12,80 kg |
| Noise classification: | Class 3 (clearly perceptible sounds) |
| Remote control | |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Bar | |
| LED type: | 4 x 1 W high-power ultra violet (UV) |
| Light effect | |
| LED type: | 2 x 3 W R/G/B |
| Spotlight | |
| LED type: | 3 x 7 W high-power 4in1 QCL RGB/WW (homogenous color mix) |
| Beam angle: | 15° |
| Beam angle (1/2 peak): | 15° |
| Beam angle (1/10 peak): | 28° |
| Illuminance in Lux (lx): | Red (R) 1m: 1022 lx, 3m: 125 lx, 6m: 33 lx Green (G) 1m: 2448 lx, 3m: 285 lx, 6m: 75 lx Blue (B) 1m: 395 lx, 3m: 47 lx, 6m: 13 lx Warm white (WW) 1m: 1892 lx, 3m: 219 lx, 6m: 58 lx All 1m: 4853 lx, 3m: 676 lx, 6m: 175 lx |
| Moving light | |
| LED type: | 1 x 15 W cold white (CW) |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

EUROLITE QuickDMX USB Wireless Transmitter/Receiver

| | |
|--------------------|--|
| Power supply: | 5V DC |
| IP classification: | IP20 |
| Power connection: | Mains input via USB A (M) connectable version |
| DMX channels: | Input 512 Output 512 |
| DMX output: | 1 x USB, type A |
| Control: | DMX; QuickDMX; plug and play |
| Range: | Range up to 400m with line-of-sight |
| Carrier frequency: | 2,4 GHz |
| Parallel mode: | Max. 6 transmitter |
| RF power output: | 23 dBm |
| Modulation: | GFSK |
| Color: | Black |
| Dimensions: | Width: 8,6 cm Depth: 4 cm Height: 1,1 cm |
| Weight: | 0,01 kg |

EUROLITE QuickDMX Wireless Transmitter

| | |
|--------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz 5V DC 1000 mA |
| IP classification: | IP20 |
| Power connection: | Mains input via coaxial power connector (M) mounting version power supply cord for USB A mains connection (provided) |
| DMX channels: | Output 512 |
| DMX input: | 1 x 3-pin XLR (M) |
| Control: | QuickDMX; DMX; plug and play |
| Range: | Range up to 400m |
| Carrier frequency: | 2,4 GHz |
| Parallel mode: | Max. 6 transmitter |
| RF power output: | 19 dBm |
| Modulation: | GFSK |
| Color: | Silver |
| Dimensions: | Length: 21,2 cm Diameter: Ø 1,8 cm |
| Weight: | 0,15 kg |

EUROLITE DMX LED Color Chief Controller

| | |
|--------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz 9V DC 800 mA |
| Power consumption: | 7,2 W |
| IP classification: | IP20 |
| Protection class: | Protection class III |
| Power connection: | Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided) |
| Programs: | Programmable 24 scenes/chases distributed over 1 page/s |
| DMX channels: | Output 240 |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Control: | DMX; sound to light via RCA (F) mounting version; sound to light via microphone |
| Housing color: | Black |
| Available storage media: | USB devices (FAT 32) |
| USB port: | Type A |
| Color: | Black |
| PC connect: | , firmware can be updated |
| Housing design: | (19") 48.3 cm rack installation 3 U Desktop console housing |
| Dimensions: | Width: 48,3 cm Depth: 13,35 cm |

| | |
|-----------------------|---------------------------|
| | Height: 8,5 cm |
| Weight: | 2,25 kg |
| Noise classification: | Class 0 (no noise at all) |

EUROLITE STV-60-WOT EU Steel Stand black

| | |
|----------------------------|------------------------------------|
| Maximum carrying capacity: | 30 kg |
| Height: | Maximum: 320 cm Minimum: 150 cm |
| Attachment system: | TV spigot Ø 28mm |
| Type (general stands): | Light stand/manual |
| Material: | Steel/magnesium |
| Color: | Black |
| Transport dimensions: | 126 cm x 12 cm x 15 cm |
| Weight: | 5,65 kg |