



**List price: 1486.31 €**

incl. 19% VAT.

### Features:

#### EUROLITE AKKU IP Flat Light 3 bk

Flat IP65 spotlight in black with 3 x 8 W 4in1 QCL RGBW LED, QuickDMX transceiver

- Integrated QuickDMX transceiver for wireless DMX control
- Battery operation up to 16h depending on program used
- 3 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via master/slave function; IR remote control; QuickDMX; stand-alone; sound to light via microphone
- Flicker-free
- With a beam angle of 15°
- With mounting bracket
- LCD display
- Suitable for outdoor use IP65
- For application areas such as: Small rental; rental; wedding/gala/events; mobile djs / entertainer
- Dimmer electronic; Dimmer speed (step response) adjustable; color blend stepless; color change adjustable; colors preset
- Strobe effect
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator
- Preprogrammed in Light 'J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
- Silent operation
- Application possibility: Standing

#### Package contents

- 1 x device, 1 x external mains adapter, 1 x power cord, 1 x remote control, 1 x battery, 1 x declaration of conformity, 1 x user manual

### Logistic

EAN / GTIN: 4026397691054

Weight: 12,50 kg

Length: 0.82 m

Width: 0.41 m

Height: 0.52 m

## ROADINGER Flightcase 4x AKKU Flat Light Series

Carrying case, PRO version

- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- Rugged carrying handle
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

Weight: 10,58 kg

---

### EUROLITE AKKU IP Flat Light 3 bk

Power supply: 100-240 V AC, 50/60 Hz  
12,6 V DC 2500 V

---

IP classification: IP65

---

Protection class: Protection class III

---

Power connection: Mains input via coaxial power connector (M)  
mounting version power supply cord with Euro  
plug (provided)  
Battery/battery pack

---

Battery pack type: 2 x lithium ion 11,1 V, 2600 mAh, 28,86 Wh

---

Battery pack: Battery operation up to 16h depending on  
program used  
Recharging time 4h

---

Lamp type: LED lamp

---

LED type: 3 x 8 W high-power 4in1 QCL RGBW  
(homogenous color mix)

---

Flash rate: 1 - 23 Hz

---

DMX channels: 3; 4; 6; 8; 10

---

Cooling: Passive convection cooling

---

Control: Master/slave function; IR remote control;  
QuickDMX; stand-alone; sound to light via  
microphone

---

Preprogrammed in: Light J; Light Captain; EASY SHOW 1; EASY  
SHOW 2; EASY SHOW 3

---

Projection: Flicker-free

---

Carrier frequency: 2,4 GHz

---

Beam angle: 15°

---

Beam angle (1/2 peak): 15°

---

Beam angle (1/10 peak): 33°

---

Housing color: Black

---

Attachment system: Mounting bracket

---

Display type:	LCD display
Dimensions:	Width: 17,2 cm Depth: 13,8 cm Height: 6,2 cm
Weight:	1,61 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

### **ROADINGER Flightcase 4x AKKU Flat Light Series**

Aluminum profile frames:	25 mm
Carrying handle:	1 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	8 cm x 19 cm x 10 cm
Accessory compartment:	38 cm x 6,5 cm x 12 cm
Inside dimensions:	38 cm x 27 cm x 12 cm
Dimensions:	Width: 42 cm Depth: 31 cm Height: 20 cm
Weight:	4,15 kg