



**List price: 1093.61 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED THA-20PC TRC Theater-Spot wh

Fanless PC spot with 17 W white light LED, color rendering index (CRI) >90

- New LED technology that simulates the color temperature curve of a halogen lamp when dimming
- Two additional frost filters provide a soft, homogeneous light
- 1 powerful LED 17 W COB (chip-on-board) Dim to warm
- The device is cooled by passive convection cooling
- Control via stand-alone; quick select potentiometer for brightness
- Flicker-free
- With a beam angle of 17°
- Very high color rendering index (CRI)
- With mounting bracket
- For application areas such as: Trade fair and shop fitting; wedding/gala/events; installation; restaurants, bars and hotels
- Dimmer electronic
- Rubber feet
- Silent operation
- Application possibility: Suspended; on stand

#### Package contents

- 1 x spotlight, 1 x user manual, 1 x barn door, 2 x frost filter

### Logistic

EAN / GTIN: 4026397694123

Weight: 20,10 kg

Length: 1.30 m

Width: 0.50 m

Height: 0.30 m

Bulky product

#### ROADINGER Flightcase 4x THA-20PC

- 6,5 mm,

- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

Weight: 17,02 kg

---

### EUROLITE LED THA-20PC TRC Theater-Spot wh

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	22 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Fuse:	5 x 20 mm, T 1 A fuse replaceable
LED type:	1 x 17 W COB (chip-on-board) Dim to warm
Cooling:	Passive convection cooling
Control:	Stand-alone; quick select potentiometer for brightness
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17° Frost filter 19° Frost filter 26°
Beam angle (1/10 peak):	36° Frost filter 40° Frost filter 53°
Color temperature:	3000K
Color rendering index (CRI):	92 Ra
Illuminance in Lux (lx):	Warm white (WW) 3m: 727 lx, 6m: 188 lx
Housing color:	White
Attachment system:	Mounting bracket
Transport aid:	Rubber feet
Dimensions:	Length: 21,5 cm Width: 14,5 cm Depth: 21 cm
Weight:	2,23 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

### ROADINGER Flightcase 4x THA-20PC

Maximum load:	50 kg
Use of brands:	Branded hardware
Device compartment:	16 cm x 19 cm x 13,5 cm
Inside dimensions:	42,5 cm x 43 cm x 18 cm
Accessory compartment:	10,5 cm x 43 cm x 18 cm
Material thickness:	6,5 mm
Dimensions:	Width: 51 cm Depth: 46 cm Height: 27 cm
Weight:	8,10 kg