



List price: 1093.61 €

incl. 19% VAT.

Features:

EUROLITE LED THA-20PC TRC Theater-Spot wh

Fanless PC spot with 17 W white light LED, color rendering index (CRI) >90

- New LED technology that simulates the color temperature curve of a halogen lamp when dimming
- Two additional frost filters provide a soft, homogeneous light
- 1 powerful LED 17 W COB (chip-on-board) Dim to warm
- The device is cooled by passive convection cooling
- Control via stand-alone; quick select potentiometer for brightness
- Flicker-free
- With a beam angle of 17°
- Very high color rendering index (CRI)
- With mounting bracket
- For application areas such as: Trade fair and shop fitting; wedding/gala/events; installation; restaurants, bars and hotels
- Dimmer electronic
- Rubber feet
- Silent operation
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x barndoor, 2 x frost filter

Logistic

EAN / GTIN: 4026397694123

Weight: 20,10 kg

Length: 1.30 m

Width: 0.50 m

Height: 0.30 m

Bulky product

ROADINGER Flightcase 4x THA-20PC

- 6,5 mm,

- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 17,02 kg

EUROLITE LED THA-20PC TRC Theater-Spot wh

| | |
|------------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 22 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Fixed power supply cord with safety plug |
| Fuse: | 5 x 20 mm, T 1 A fuse replaceable |
| LED type: | 1 x 17 W COB (chip-on-board) Dim to warm |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; quick select potentiometer for brightness |
| Projection: | Flicker-free |
| Beam angle: | 17° |
| Beam angle (1/2 peak): | 17° Frost filter 19° Frost filter 26° |
| Beam angle (1/10 peak): | 36° Frost filter 40° Frost filter 53° |
| Color temperature: | 3000K |
| Color rendering index (CRI): | 92 Ra |
| Illuminance in Lux (lx): | Warm white (WW) 3m: 727 lx, 6m: 188 lx |
| Housing color: | White |
| Attachment system: | Mounting bracket |
| Transport aid: | Rubber feet |
| Dimensions: | Length: 21,5 cm Width: 14,5 cm Depth: 21 cm |
| Weight: | 2,23 kg |
| Noise classification: | Class 0 (no noise at all) |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 4x THA-20PC

| | |
|------------------------|---|
| Maximum load: | 50 kg |
| Use of brands: | Branded hardware |
| Device compartment: | 16 cm x 19 cm x 13,5 cm |
| Inside dimensions: | 42,5 cm x 43 cm x 18 cm |
| Accessory compartment: | 10,5 cm x 43 cm x 18 cm |
| Material thickness: | 6,5 mm |
| Dimensions: | Width: 51 cm Depth: 46 cm Height: 27 cm |
| Weight: | 8,10 kg |