



List price: on demand €

incl. 19% VAT.

Features:

- Positioning within TILT
- <p>FUTURELIGHT DMH-160 MK2 LED Moving Head
- <p class="featureSatz">PRO moving head with 200 W COB LED and extensive features
- Effect wheel with rotating 3-facet prism and 8-facet prism and frost filter
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- 1 powerful LED 200 W COB (chip-on-board) cold white (CW)
- Positioning within 630° PAN, 270° TILT
- Iris stepless; gobo wheel with rotating gobos; gobo wheel with static gobos; prism 3-fold; prism 8-fold; focus motor-driven; frost filter; color wheel
- Gobo effect; beam effect; strobe effect
- Color wheel with 8 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 7 gobos and open
- Shake effect
- Gobo wheel with rotating gobos, 7 gobos and open
gobos changeable
- Shake effect
- Gobos changeable
- Slot-in gobo system for easy gobo replacement
- The device is cooled by temperature-controlled fan
- Control via stand-alone; RDM; DMX; sound to light via microphone
- Flicker-free
- With a beam angle of 11°
- LCD display,
with battery buffering for easy controlling upgradeable
- Built with NEUTRIK connector

Logistic

EAN / GTIN: 4026397712919

Weight: 115,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- Exact 16 bit resolution at Dimmer
- Pulse-width modulation variable
- Preprogrammed in LED PC-Control 512; Light Captain
- With omega bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; rental
- Application possibility: Standing; suspended

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 2 x omega bracket, 1 x XLR cable, 1 x declaration of conformity
- <p>ROADINGER Flightcase 4x DMH-90/150/DMB-160/PLB-230
- <p class="featureSatz">Trunk case with castors, PRO version
- For optimal security
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 8 hinged, chromium plated case handles
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 113,60 kg

FUTURELIGHT DMH-160 MK2 LED Moving Head

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	285 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Fuse:	5 x 20 mm, T 3,15 A
Lamp type:	LED lamp
LED type:	1 x 200 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	270°
Max. PAN movement:	630°
Equipment:	Iris stepless; gobo wheel with rotating gobos; gobo wheel with static gobos; prism 3-fold; prism 8-fold; focus motor-driven; frost filter; color wheel
Color generation:	Color wheel with 8 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 7 gobos and open Shake effect Gobo wheel with rotating gobos, 7 gobos and open

Outside diameter 27mm
Image diameter 22mm
Gobos changeable
Shake effect
Gobos changeable
Slot-in gobo system for easy gobo replacement

DMX channels:	14; 16; 23; 25
DMX input:	1 x 5-pin XLR (M) mounting version 1 x 3-pin XLR (M) mounting version
DMX output:	1 x 5-pin XLR (F) mounting version 1 x 3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; RDM; DMX; sound to light via microphone
Preprogrammed in:	LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	11°
Beam angle (1/2 peak):	11°
Illuminance in Lux (lx):	Cold white (CW) 3m: 27074 lx, 6m: 6796 lx
Housing color:	Black
Attachment system:	2x omega bracket
Display type:	LCD display battery buffering upgradeable
Use of brands:	Built with NEUTRIK connector
Color:	Black
Dimensions:	Width: 34,3 cm Depth: 26,2 cm Height: 44,1 cm
Weight:	15,85 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x DMH-90/150/DMB-160/PLB-230

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	8 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	29,5 cm x 27 cm x 41 cm
Middle compartment:	9,5 cm x 54 cm x 46,5 cm
Inside dimensions:	94,5 cm x 56 cm x 46,5 cm
Dimensions:	Width: 102,5 cm

Depth: 60,5 cm
Height: 72 cm

Weight: 41,90 kg
