



List price: 700.91 €

incl. 19% VAT.

Features:

EUROLITE LED KLS Laser Bar FX Light Set wh

Bar with 2 derbies, 2 spots, white strobe LEDs, laser (RG, 2M), foot switch

- Compact lightweight
 - Crossbar with integrated DMX control unit and stand sleeve
 - 2 laser diodes project hundreds of red and green laser beams
 - Two rotating derbies for mirror ball effects with three bright LEDs (red, green and blue) each
 - For application areas such as: Wedding/gala/events; mobile use; clubs/dancing school; party room; mobile djs / entertainer
 - When fog is used, this effect becomes especially attractive
 - 37 integrated show programs
 - Control via wireless footswitch; IR remote control; DMX; master/slave function; sound to light via microphone; W-DMX by wireless solution via USB (optional); QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); stand-alone
 - With mounting bracket
 - Mains input and output for power linking up to 8 units
 - Preprogrammed in Light´J; EASY SHOW 1; LED PC-Control 512; Light Captain; Colorchief
 - Application possibility: On stand
- laser**
- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
- spotlight**
- 3 powerful LEDs 3 W high-power 3in1 TCL RGB (homogenous color mix)
 spots controlled separately
- light effect**
- 3 powerful LEDs 1 W high-power R/G/B
 - Flower effect; multi beam effect

Logistic

EAN / GTIN: 4026397699821

Weight: 30,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

bar

- 4 powerful LEDs 1 W high-power cold white (CW)
- Strobe effect

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x declaration of conformity, 1 x foot control, 1 x remote control, 2 x battery, 2 x mounting bracket, 1 x bag, 2 x knurled screw, 2 x washer

OMNITRONIC BPS-3 Loudspeaker Stand white

XL speaker/lighting stand with square base, height adjustable 136-230 cm, max. load 18 kg

- Rugged, square base plate (55 x 55 cm)
- 3 x M20 thread for off-center installation
- Reinforcing sleeves for an optimal base-to-pole connection
- 35 mm extension tube with M10 thread for light fixtures

Technical specifications:

Weight: 25,45 kg

EUROLITE LED KLS Laser Bar FX Light Set wh

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	5 x 20 mm, F 1 A fuse replaceable
Lamp type:	LED lamp
Flash rate:	0 - 30 Hz
DMX channels:	3; 5; 9; 19; 27
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Wireless footswitch; IR remote control; DMX; master/slave function; sound to light via microphone; W-DMX by wireless solution via USB (optional); QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); stand-alone
Preprogrammed in:	Light J; EASY SHOW 1; LED PC-Control 512; Light Captain; Colorchief
Housing color:	White
Attachment system:	2x mounting bracket
Dimensions:	Width: 103 cm Depth: 6,1 cm Height: 38,7 cm
Weight:	9,05 kg

Noise classification:	Class 2 (slight noise)
Foot control	
Battery:	1 x 9.0 V E block 6LR61 alkaline manganese included
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Spotlight	
LED type:	3 x 3 W high-power 3in1 TCL RGB (homogenous color mix)
Laser	
Laser class:	2M
Laser color:	R/G
Laser module:	Red (R) 100 mW 650nm Green (G) 30 mW 532nm
Light effect	
LED type:	3 x 1 W high-power R/G/B
Bar	
LED type:	4 x 1 W high-power cold white (CW)

OMNITRONIC BPS-3 Loudspeaker Stand white

Weight:	13,61 kg
---------	----------