



List price: 379.61 €

incl. 19% VAT.

Features:

EUROLITE LED PFR-50 WW Fresnel Spot

Compact spotlight with 20 W COB LED, manual zoom, color rendering index (CRI) >95

- 1 powerful LED 20 W COB (chip-on-board) warm white (WW)
- With fresnel lens
- With a beam angle of 11° - 40°
- Flicker-free
- The device is cooled by cooling fan
- Very high color rendering index (CRI)
- Control via stand-alone; DMX (optional); master/slave function (optional)
- For application areas such as: Trade fair and shop fitting; installation; theater; rental
- Very quiet working noise
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x power cord, 1 x barn door, 1 x plug (male), 1 x user manual

EUROLITE DMX-Interface for LED PFE-50

Control unit with DMX interface for EUROLITE LED PFE-50 3000 K Profile Spot

- Adds full DMX functionality to the spotlight
- Control via DMX; master/slave function
- Dimmer electronic
- Strobe effect
- 4 digit 7-segment LED display

Package contents

- 1 x device, 1 x USB cable, 4 x screw

Logistic

EAN / GTIN: 4026397581522

Weight: 3,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Technical specifications:

Weight: 2,06 kg

EUROLITE LED PFR-50 WW Fresnel Spot

| | |
|------------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 48 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via 3-pin screw plug connector (M) mounting version power supply cord with safety plug (provided) |
| Power output: | 3-pin screw plug connector (F) mounting version |
| Fuse: | 5 x 20 mm, T 1 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 1 x 20 W COB (chip-on-board) warm white (WW) |
| Cooling: | Cooling fan |
| Control: | Stand-alone; DMX (optional); master/slave function (optional) |
| Projection: | Flicker-free |
| Beam angle: | 11° - 40° |
| Beam angle (1/2 peak): | 11 - 30° |
| Beam angle (1/10 peak): | 21 - 40° |
| Color temperature: | 3100K |
| Color rendering index (CRI): | 96 Ra |
| Illuminance in Lux (lx): | Narrow warm white (WW) 1m: 20302 lx, 3m: 2529 lx, 6m: 667 lx Wide warm white (WW) 1m: 5751 lx, 3m: 748 lx, 6m: 207 lx |
| Housing color: | Black |
| Material: | Plastic; aluminum |
| Slot for spot length: | Ø 11 cm |
| Dimensions: | Length: 30,5 cm Width: 16,0 cm Height: 22,0 cm |
| Weight: | 1,94 kg |
| Noise classification: | Class 1 (very slight noise, suitable for noise-sensitive environments) |
| Mounting bracket | |
| Diameter mounting holes: | 1 x Ø11mm; 2 x Ø8mm; 4 x Ø4mm |
| Material: | Aluminum, 3 mm |
| Power cord | |
| Cable construction: | 3 x 0,75 mm ² H05VV-F |

| | |
|----------------------|--|
| Cable length: | Approx. 1,4 m |
| Barndoor | |
| Material: | Metal, 1 mm |
| Ring diameter: | Outside: 99 mm Inside: 90 mm |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

EUROLITE DMX-Interface for LED PFE-50

| | |
|--------------------|-------------------------------|
| IP classification: | IP20 |
| DMX channels: | 2 |
| Control: | DMX; master/slave function |
| Housing color: | Black |
| Display type: | 4 digit 7-segment LED display |
| Weight: | 0,12 kg |