



**List price: 1046.01 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED TSL-350 Scan COB wh

Handy scanner with 60 W COB LED, gobo and color wheel

- Compact design
- 1 powerful LED 60 W COB (chip-on-board) cold white (CW)
- Positioning within TILT
- Color wheel; gobo wheel with rotating gobos; focus manual
- Color wheel with 7 dichroic filters plus open<BR>half colors selectable, Rainbow effect with adjustable speed
- Gobo wheel with rotating gobos, 7 gobos and open<BR>slot-in gobo system for easy gobo replacement
- Shake effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 11°
- LCD display
- Dimmer electronic
- Preprogrammed in Light'J; Light Captain; EASY SHOW 2; EASY SHOW 3
- Rubber feet
- For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

#### Package contents

### Logistic

EAN / GTIN: 4026397704426

Weight: 17,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x mounting bracket, 3 x gobos

### ROADINGER Flightcase 2x TSL-150/250/350

#### Trunk case

- High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding<BR>cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- 4 rubber feet
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Technical specifications:

---

Weight: 13,42 kg

---

### EUROLITE LED TSL-350 Scan COB wh

|                    |   |
|--------------------|---|
| Power supply:      | 100-240 V AC, 50/60 Hz  |
| Power consumption: | 70 W  |
| IP classification: | IP20  |
| Protection class:  | Protection class I  |
| Power connection:  | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)  |
| Fuse:              | 5 x 20 mm, T 1,5 A fuse replaceable   |
| Lamp type:         | LED lamp  |
| LED type:          | 1 x 60 W COB (chip-on-board) cold white (CW)  |
| Equipment:         | Color wheel; gobo wheel with rotating gobos; focus manual   |
| Color generation:  | Color wheel with 7 dichroic filters plus open<br>Half colors selectable, Rainbow effect with adjustable speed   |
| Gobos:             | Gobo wheel with rotating gobos, 7 gobos and open<br>Outside diameter 10mm<br>Image diameter 14mm<br>Slot-in gobo system for easy gobo replacement<br>Shake effect                         |
| DMX channels:      | 10  |
| DMX input:         | 3-pin XLR (M) mounting version  |
| DMX output:        | 3-pin XLR (F) mounting version  |
| Cooling:           | Cooling fan   |
| Control:           | Stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |

---

|                          |   |
|--------------------------|---|
| Preprogrammed in:        | Light J; Light Captain; EASY SHOW 2; EASY SHOW 3      |
| Projection:              | Flicker-free  |
| Beam angle:              | 11°   |
| Beam angle (1/2 peak):   | 11°   |
| Illuminance in Lux (lx): | Cold white (CW) 1m: 12034 lx, 3m: 1489 lx, 6m: 388 lx |
| Housing color:           | White   |
| Display type:            | LCD display   |
| Transport aid:           | Rubber feet   |
| Dimensions:              | Width: 16,0 cm<br>Depth: 15,0 cm<br>Height: 33,0 cm   |
| Weight:                  | 3,26 kg   |

### **ROADINGER Flightcase 2x TSL-150/250/350**

|                          |   |
|--------------------------|---|
| Maximum load:            | 50 kg   |
| Aluminum profile frames: | 30 mm   |
| Case handle:             | 2 pc/pcs  |
| Stop hinge:              | 2 pc/pcs  |
| Lock:                    | Butterfly lock: 2 pc/pcs with shut-off function |
| Transport aid:           | 4 x rubber feet                                 |
| Material:                | Plywood multi-layer glued, 7 mm                 |
| Color:                   | Black, laminated                                |
| Device compartment:      | 19 cm x 33,5 cm x 12,5 cm                       |
| Accessory compartment:   | 8 cm x 33 cm x 12,5 cm                          |
| Inside dimensions:       | 49 cm x 33,5 cm x 12,5 cm                       |
| Dimensions:              | Width: 54 cm<br>Depth: 38 cm<br>Height: 24 cm   |
| Weight:                  | 6,90 kg   |