



16 x



List price: 3925.81 €

incl. 19% VAT.

Features:

EUROLITE LED Silent Par 6 QCL floor bk

LED floor spot with RGB/WW color mixing

- 14350 lux at 1 m
- 6 powerful LEDs 8 W 4in1 QCL RGB/WW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- Direct color selection for 25 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone
- Flicker-free
- With a beam angle of 16°
- With double bracket; with mounting bracket
- 4 digit 7-segment LED display
- Preprogrammed in Light´J; Light Captain
- For application areas such as: Clubs/dancing school; wedding/gala/events; Trade fair and shop fitting; stage; theater; restaurants, bars and hotels; mobile djs / entertainer
- Silent operation
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x XLR cable

Logistic

EAN / GTIN: 4026397687071

Weight: 80,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

ROADINGER Flightcase BAS-1 8x SILENT PAR 6 QCL FLOOR

Trunk case with castors, PRO version

- High-quality workmanship with birch multiplex 10 mm, black, laminated
- Interior with felt cover
cover with foam padding
- Aluminum profile frames 32mm with rounded edges
- 4 hinged, chromium plated case handles
- 4 high-quality butterfly locks
- 4 castors with 2 locking brakes
- Branded hardware
- 2 Edge mounting handles
- 4 built-in stacking trays in the cover
- Made in Europe

ROADINGER Flightcase Extension 8x SILENT PAR 6 QCL FLOOR for BAS-1

- High-quality workmanship with birch multiplex 10 mm, black
- Interior with felt cover
cover with foam padding
- 4 hinged, chromium plated case handles
- 4 high-quality butterfly locks
- Branded hardware
- Made in Europe

Technical specifications:

Weight: 76,58 kg

EUROLITE LED Silent Par 6 QCL floor bk

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	45 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (gray), mounting version
LED type:	6 x 8 W 4in1 QCL RGB/WW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	6; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone
Preprogrammed in:	Light J; Light Captain
Projection:	Flicker-free
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	29°
Housing color:	Black

Attachment system:	Double bracket Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 14,3 cm Width: 17,7 cm Height: 21,1 cm
Weight:	2,15 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase BAS-1 8x SILENT PAR 6 QCL FLOOR

Aluminum profile frames:	32 mm
Case handle:	4 pc/pcs
Edge mounting handle:	2 pc/pcs
Lock:	Butterfly lock: 4 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Use of brands:	Branded hardware
Material:	Birch multiplex, 10 mm
Color:	Black, laminated
Device compartment:	14,5 cm x 15 cm x 19 cm
Accessory compartment:	65,5 cm x 11 cm x 19 cm
Dimensions:	Length: 70 cm Width: 48 cm Height: 43,5 cm
Weight:	23,75 kg

ROADINGER Flightcase Extension 8x SILENT PAR 6 QCL FLOOR for BAS-1

Case handle:	4 pc/pcs
Lock:	Butterfly lock: 4 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 10 mm
Color:	Black
Device compartment:	14,5 cm x 15 cm x 16 cm
Accessory compartment:	66 cm x 11,5 cm x 16 cm
Dimensions:	Length: 69 cm Width: 47 cm Height: 29 cm
Weight:	13,40 kg