



List price: on demand €

incl. 19% VAT.

Features:

FUTURELIGHT EYE-1940 QCL Zoom LED Moving Head Wash

PRO Washlight with 19 Osram Ostar 40W RGBW LEDs, large zoom range and pixel control

- 19 powerful LEDs 40 W 4in1 QCL RGBW (homogenous color mix) LEDs controlled separately
- OSRAM LED installed
- Variable color temperature 2800 K - 10000 K
- Positioning within 540° PAN, 230° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Exact 16 bit resolution at Dimmer, color, zoom
- The device is cooled by temperature-controlled fan at the Head; low-noise cooling fan at the base
- Control via stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by LumenRadio upgradeable; RDM; sound to light via microphone
- Flicker-free
- Multicolor LCD display, with battery buffering for easy controlling upgradeable
- Zoom motor driven
- Patterns animated; foreground color adjustable; background color adjustable; dimmer curves with adjustable response; pulse-width modulation variable; pulse effect adjustable; white balance; scenes user-definable; CTO correction filter virtual; Dim to warm; colors preset; Dimmer speed (step response) adjustable
- With omega bracket
- Rubber feet
- Mains input and output for power linking up to 4 units
- For application areas such as: Wedding/gala/events; stage; theater; rental

Logistic

EAN / GTIN: 4026397696431

- Preprogrammed in Light Captain
- With a beam angle of 1° - 42°
- Very quiet working noise
- Application possibility: Standing; suspended

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 2 x omega bracket, 1 x XLR cable

ROADINGER Flightcase 2x EYE-1940 with wheels

Trunk case with castors

- With 1 accessory compartment
- With 2 device compartments
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- 4 built-in stacking trays in the cover
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

FUTURELIGHT EYE-1940 QCL Zoom LED Moving Head Wash

| | |
|---------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 530 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via IP T-Con (M) mounting version power supply cord with safety plug |
| Power output: | IP T-Con (F) mounting version |
| Device fuse: | 5 x 20 mm, T 3,15 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 19 x 40 W 4in1 QCL RGBW (homogenous color mix) |
| LED manufacturer: | OSRAM |
| Max. TILT movement: | 230° exact positioning (16 bit resolution) auto position correction (feedback) |
| Max. PAN movement: | 540° exact positioning (16 bit resolution) auto position correction (feedback) |
| Flash rate: | 1 - 16 Hz |
| Equipment: | Zoom motor driven |
| DMX channels: | 18; 25; 37; 30; 37; 49; 94; 101; 113 |
| DMX input: | 3-pin XLR (M) mounting version IP 5-pin XLR (M) mounting version IP |
| DMX output: | 3-pin XLR (F) mounting version IP 5-pin XLR (F) mounting version IP |
| Cooling: | 2 x temperature-controlled fan at the Head 1 x low-noise cooling fan at the base |

| | |
|--------------------------|---|
| Control: | Stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by LumenRadio upgradeable; RDM; sound to light via microphone |
| Preprogrammed in: | Light Captain |
| Projection: | Flicker-free |
| Beam angle: | 1° - 42° |
| Beam angle (1/2 peak): | 1 - 24° |
| Beam angle (1/10 peak): | 5 - 42° |
| Color temperature: | 2800K - 10000K adjustable |
| Illuminance in Lux (lx): | Narrow red (R) 1m: 15042 lx, 3m: 11510 lx, 6m: 3434 lx Narrow green (G) 1m: 30205 lx, 3m: 19403 lx, 6m: 5390 lx Narrow blue (B) 1m: 5115 lx, 3m: 3767 lx, 6m: 1836 lx Narrow cold white (CW) 1m: 67510 lx, 3m: 42444 lx, 6m: 11973 lx Narrow all 3m: 69714 lx, 6m: 20470 lx Wide red (R) 1m: 4425 lx, 3m: 533 lx, 6m: 141 lx Wide green (G) 1m: 6498 lx, 3m: 823 lx, 6m: 226 lx Wide blue (B) 1m: 1972 lx, 3m: 321 lx, 6m: 90 lx Wide cold white (CW) 1m: 14186 lx, 3m: 1779 lx, 6m: 491 lx Wide all 1m: 24550 lx, 3m: 3126 lx, 6m: 865 lx |
| Housing color: | Black |
| Attachment system: | Omega bracket |
| Display type: | Multicolor LCD display battery buffering upgradeable |
| Transport aid: | Rubber feet |
| Dimensions: | Width: 40 cm Depth: 28 cm Height: 42,2 cm |
| Weight: | 17,10 kg |
| Noise classification: | Class 1 (very slight noise, suitable for noise-sensitive environments) |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 2x EYE-1940 with wheels

| | |
|--------------------------|-----------------------------------|
| Maximum load: | 100 kg |
| Aluminum profile frames: | 30 mm |
| Case handle: | 4 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Transport aid: | 4 x castors with 2 locking brakes |

| | |
|------------------------|---|
| | 4 x built-in stacking trays in the cover |
| Color: | Black, laminated |
| Accessory compartment: | 60 cm x 11,5 cm x 39 cm |
| Device compartment: | 29 cm x 40,5 cm x 39 cm |
| Material thickness: | 10 mm |
| Dimensions: | Width: 65 cm Depth: 60 cm Height: 65,5 cm |
| Weight: | 29,60 kg |