

## EUROLITE AKKU PLL-168 WW/CW Panel

Battery-powered surface light with 168 dual white LEDs, QuickDMX port and barn doors

Art. No.: 40001845

GTIN: 4026397703016



**List price: 391.51 €**

incl. 19% VAT.

### Features:

- 84 powerful LEDs 0,5 W SMD 2835 cold white (CW)
- 84 powerful LEDs 0,5 W SMD 2835 warm white (WW)
- Variable color temperature 2800 K - 6500 K
- 4 barn doors to avoid blinding the audience and for protection during transport
- Dimmer electronic; pulse-width modulation variable; Energy-saving mode
- Battery operation up to 8h depending on program used
- Integrated show programs
- Direct color selection for 38 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; sound to light via microphone; master/slave function; DMX; quick select potentiometer for brightness and color temperature; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 120°
- Very high color rendering index (CRI)
- With mounting bracket
- Slim, rugged metal housing
- 4 digit 7-segment LED display
- Preprogrammed in Light Captain
- Cordless, flexible and versatile
- Mains input and output for power linking up to 8 units
- For application areas such as: Video and photography; stage; mobile use; small rental
- Silent operation
- Application possibility: Suspended; on stand

### Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord

### Logistic

EAN / GTIN: 4026397703016

Weight: 3,90 kg

Length: 0.40 m

Width: 0.25 m

Height: 0.15 m

## Technical specifications:

|                              |  |
|------------------------------|--|
| Power supply:                | 100-240 V AC, 50/60 Hz   |
| IP classification:           | IP20   |
| Protection class:            | Protection class I   |
| Power connection:            | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug (provided)  |
| Power output:                | P-Con (gray), mounting version   |
| Fuse:                        | 5 x 20 mm, T 1 A fuse replaceable  |
| Battery pack type:           | 1 x lithium ion 22,2 V, 4400 mAh, 97,68 Wh   |
| Battery pack:                | Battery operation up to 8h depending on program<br>used<br>Recharging time 4h  |
| Lamp type:                   | LED lamp   |
| LED type:                    | 84 x 0,5 W SMD 2835 cold white (CW)<br>84 x 0,5 W SMD 2835 warm white (WW)   |
| Flash rate:                  | 0 - 20 Hz  |
| DMX channels:                | 2; 4; 6  |
| DMX input:                   | 3-pin XLR (M) mounting version   |
| DMX output:                  | 3-pin XLR (F) mounting version   |
| Cooling:                     | Passive convection cooling   |
| Control:                     | Stand-alone; sound to light via microphone;<br>master/slave function; DMX; quick select<br>potentiometer for brightness and color<br>temperature; QuickDMX via USB (optional); W-<br>DMX by wireless solution via USB (optional);<br>CRMX by LumenRadio via USB (optional) |
| Preprogrammed in:            | Light Captain  |
| Projection:                  | Flicker-free   |
| Beam angle:                  | 120°   |
| Beam angle (1/2 peak):       | 120°   |
| Color temperature:           | 2800K - 6500K adjustable   |
| Color rendering index (CRI): | 92 Ra  |
| Housing color:               | Black  |
| Attachment system:           | Mounting bracket   |
| Display type:                | 4 digit 7-segment LED display  |
| Dimensions:                  | Width: 35,7 cm<br>Depth: 11,7 cm<br>Height: 22,0 cm  |
| Weight:                      | 3,60 kg  |
| Noise classification:        | Class 0 (no noise at all)  |
| Photobiological safety:      | Risk Group 0   |
| Legal specifications         |  |
| Special product:             | Not designed for household room illumination   |
| Intended use:                | Show effect lighting   |