

EUROLITE LED PLL-360 3200K Panel

Surface light with 360 warm white (WW)LEDs and DMX

Art. No.: 40001890

GTIN: 4026397616804



List price: 474.81 €

incl. 19% VAT.

Features:

- 360 powerful LEDs 0,5 W SMD 2835 warm white (WW)
- Energy-saving, durable and environmentally friendly
- Frost filter provides a soft, homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- Silent operation
- Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by passive convection cooling
- Control via quick select potentiometer for brightness; DMX; master/slave function
- Flicker-free
- With a beam angle of 120°
- Very high color rendering index (CRI)
- With mounting bracket
- LCD display
- Slim, rugged metal housing
- For application areas such as: Video and photography; stage; Trade fair and shop fitting; theater
- Various versions available
- Dimmable
- Mains input and output for power linking up to 8 units
- Rugged carrying handle
- Application possibility: Suspended; on stand
- Preprogrammed in Light J; Light Captain; Colorchief

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord

Logistic

EAN / GTIN: 4026397616804

Weight: 6,95 kg

Length: 0.63 m

Width: 0.15 m

Height: 0.37 m

Technical specifications:

| | |
|----------------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 130 W |
| IP classification: | IP20 |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output: | IEC connector (F) mounting version |
| Lamp type: | LED lamp |
| Lamp specification: | Dimmable |
| LED type: | 360 x 0,5 W SMD 2835 warm white (WW) |
| DMX channels: | 3 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Quick select potentiometer for brightness; DMX; master/slave function |
| Preprogrammed in: | Light J; Light Captain; Colorchief |
| Projection: | Flicker-free |
| Beam angle: | 120° |
| Beam angle (1/2 peak): | 120° |
| Color temperature: | 3200K |
| Color rendering index (CRI): | 94 Ra |
| Illuminance in Lux (lx): | Warm white (WW) 3m: 403 lx, 6m: 118 lx |
| Luminous flux: | 9367 lm |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Display type: | LCD display |
| Carrying handle: | 1 pc/pcs |
| Dimensions: | Width: 57 cm Depth: 12 cm Height: 31 cm |
| Weight: | 6,10 kg |
| Noise classification: | Class 0 (no noise at all) |
| Energy efficiency class (A - G): | F |
| EPREL-Nr: | 1056205 |