# eurolite®

## EUROLITE LED PFE-100 RGBW Profile Spot
PRO profile spotlight, 100 W 4in1 LED (RGBW), zoom, shutter blades

**Art. No.: 40001982**
GTIN: 4026397557015

## List price: 784.21 €
incl. 19% VAT.

## Features:

- 1 powerful LED 100 W COB (chip-on-board) 4in1 QCL RGBW
- Focus manual
- With a beam angle of 14° - 41°
- Dimmer electronic; color blend stepless; color change adjustable; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; master/slave function
- With mounting bracket
- For application areas such as: Stage; installation; video and photography
- Preprogrammed in LED PC-Control 512; Light Captain
- OLED display
- Mains input and output for power linking up to 8 units
- Application possibility: Suspended; on stand
  **Package contents**
- 1 x spotlight, 1 x power cord, 1 x filter frame, 1 x plug (male), 1 x user manual

## Logistic

EAN / GTIN: 4026397557015
Weight: 12,85 kg
Length: 0.74 m
Width: 0.36 m
Heigh: 0.34 m

## Technical specifications:

| | |
|---|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| IP classification: | IP20 |
| Protection class: | Protection class I |

| | |
|---|---|
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x P-Con (gray), mounting version |
| Lamp type: | LED lamp |
| LED type: | 1 x 100 W COB (chip-on-board) 4in1 QCL RGBW |
| Flash rate: | 0,5 - 10 Hz |
| Equipment: | Focus manual |
| DMX channels: | 9 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | Stand-alone; DMX; master/slave function |
| Preprogrammed in: | LED PC-Control 512; Light Captain |
| PWM frequency: | 2300 Hz |
| Beam angle: | 14° - 41° |
| Beam angle (1/2 peak): | 14 - 41° |
| Beam angle (1/10 peak): | 14 - 41° |
| Lamp life: | 50000 h |
| Luminous flux: | 11500 lm |
| Housing color: | Black matte |
| Attachment system: | Mounting bracket |
| Display type: | OLED display |
| Diameter mounting holes: | 2 x Ø13mm |
| Material: | Aluminum casting; metal |
| Dimensions: | Length: 61,5 cm<br>Width: 28 cm<br>Height: 42 cm |
| Weight: | 11,10 kg |
| Noise classification: | Class 2 (slight noise) |
| Energy efficiency class (A - G): | F |
| EPREL-Nr: | 1243754 |
| Power cord | |
| Cable construction: | 3 x 1,5 mm² H05VV-F |
| Cable length: | Approx. 1,2 m |
| Mounting bracket | |
| Diameter mounting holes: | 1 x Ø12mm |
| Material: | Aluminum casting, 7 mm |
| Filter frame | |
| Diameter mounting holes: | 4 x Ø18mm |
| Material: | Aluminum, 1 mm |
| Color: | Black, matte |
| Plug (male) | |
| Color: | White; blue |