# eurolite®

### EUROLITE LED Theatre COB 100 UV

LED theatre spot with ultra violet (UV) 100 W COB (chip-on-board) LED

Art. No.: 41602020 GTIN: 4026397702378











## List price: 296.31 €

incl. 19% VAT.

#### Features:

- 1 powerful LED 100 W COB (chip-on-board) ultra violet (UV)
- UV effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
- Flicker-free
- With a beam angle of 40°
- 4 digit 7-segment LED display
- Dimmer electronic
- Preprogrammed in Light 'J; Light Captain; Colorchief
- Mains input and output for power linking up to 8 units
- With double bracket
- For application areas such as: Clubs/dancing school; stage; theater; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand
- Package contents
- 1 x spotlight, 1 x power cord, 1 x user manual

#### Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	85 W
IP classification:	IP20

#### Logistic

EAN / GTIN: 4026397702378 Weight: 3,10 kg Length: 0.26 m Width: 0.23 m Heigth: 0.34 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) ultra violet (UV)
Flash rate:	0 - 20 Hz
DMX channels:	1; 4
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional); W- DMX by wireless solution via USB (optional)
Preprogrammed in:	Light J; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	40°
Beam angle (1/2 peak):	40°
Beam angle (1/10 peak):	70°
Illuminance in Lux (lx):	Ultra violet (UV) 1m: 38 lx, 3m: 6 lx, 6m: 2 lx
Wavelength:	Ultra violet (UV) 402 nm
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 24,3 cm Depth: 31,1 cm Height: 32,0 cm
Weight:	2,75 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting