eurolite®

EUROLITE LED THA-40PC TRC Theater Spot bk

Fanless PC spot with 57 W white light LED, color rendering index (CRI) >90

Art. No.: 41602082 GTIN: 4026397621631









List price: 272.51 €

incl. 19% VAT.

Features:

- Rugged metal housing
- 1 powerful LED 57 W COB (chip-on-board) warm white (WW)
- Dimmer electronic
- The device is cooled by passive convection cooling
- Control via stand-alone; rotary dial for brightness; Dimmer
- Flicker-free
- With a beam angle of 12° 47°
- Very high color rendering index (CRI)
- With mounting bracket
- Silent operation
- For application areas such as: Trade fair and shop fitting; wedding/gala/events; restaurants, bars and hotels; video and photography
- Rubber feet
- Package contents
- 1 x spotlight, 1 x barndoor, 1 x filter frame, 1 x user manual

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	40 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug

Logistic

EAN / GTIN: 4026397621631 Weight: 4,30 kg Length: 0.34 m Width: 0.27 m Heigth: 0.22 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Fuse:	5 x 20 mm, T 1 A fuse replaceable
LED type:	1 x 57 W COB (chip-on-board) warm white (WW)
Cooling:	Passive convection cooling
Control:	Stand-alone; rotary dial for brightness; Dimmer
Projection:	Flicker-free
Beam angle:	12° - 47°
Beam angle (1/2 peak):	12 - 36°
Beam angle (1/10 peak):	18 - 47°
Color temperature:	3100K
Color rendering index (CRI):	92 Ra
Illuminance in Lux (lx):	Narrow 3m: 2008 lx, 6m: 514 lx Wide 3m: 482 lx, 6m: 141 lx
Housing color:	Black
Attachment system:	Mounting bracket
Transport aid:	Rubber feet
Material:	Aluminum casting
Slot for spot length:	13,1 cm x 13,1 cm
Dimensions:	Length: 26 cm Width: 20 cm
	Depth: 25 cm
Weight:	3,82 kg
Noise classification:	Class 0 (no noise at all)
Mounting bracket	
Diameter mounting holes:	1 x Ø10mm; 2 x Ø6mm
Material:	Metal, 3 mm
Power cord	
Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	Approx. 1 m
Barndoor	
Material:	Aluminum, 1,5 mm; metal
Ring diameter:	Outside: 12,9 mm
	Inside: 10,9 mm
Filter frame	
Diameter mounting holes:	1 x Ø4mm
Shape:	Octagonal
Material:	Aluminum, 0,8 mm
Dimensions:	Width: 13 cm Height: 13 cm Diameter: Ø 10,5 cm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting