eurolite®

EUROLITE LED THA-60PC Theater Spot

Spot with 60 W COB LED (RGBW) and plano-convex lens, extremely quiet, DMX

Art. No.: 41602110 GTIN: 4026397566604









List price: 427.21 €

incl. 19% VAT.

Features:

- With plano-convex lens
- Compact design
- 1 powerful LED 60 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX
- Flicker-free
- With a beam angle of 7° 48°
- With mounting bracket
- LCD display
- Dimmer electronic; color change adjustable; color fade adjustable; dimmer curves with adjustable response; Dimmer speed (step response) adjustable
- Strobe effect

- Preprogrammed in Light J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Colorchief

- Very quiet working noise
- For application areas such as: Clubs/dancing school; Trade fair and shop fitting; stage; theater
- Application possibility: Suspended; on stand
- Package contents
- 1 x spotlight, 1 x barndoor, 1 x user manual, 1 x filter frame

Technical specifications: Power supply: 100-240 V AC, 50/60 Hz Power consumption: 60 W

Logistic

EAN / GTIN: 4026397566604 Weight: 4,19 kg Length: 0.36 m Width: 0.21 m Heigth: 0.27 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power connection: Fixed power supply cord with safety plug LED type: 1 x 60 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix) DMX channels: 5; 6; 7 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Temperature-controlled fan Control: Stand-alone; DMX Preprogrammed in: Light'J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Colorchief Projection: Flicker-free Beam angle: 7° - 48° Beam angle (1/10 peak): 14 - 48° Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Legal specifications Special product: Special product: Not designed for household room illumination	IP classification:	IP20
Image: Color mix (homogenous color mix) DMX channels: 5; 6; 7 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Temperature-controlled fan Control: Stand-alone; DMX Preprogrammed in: Light'J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Colorchief Projection: Flicker-free Beam angle: 7° - 48° Beam angle (1/12 peak): 7 - 39° Beam angle (1/10 peak): 14 - 48° Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Legal specifications Special product:	Power connection:	Fixed power supply cord with safety plug
DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Temperature-controlled fan Control: Stand-alone; DMX Preprogrammed in: Light'J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Colorchief Projection: Flicker-free Beam angle: 7° - 48° Beam angle (1/2 peak): 7 - 39° Beam angle (1/10 peak): 14 - 48° Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Legal specifications Special product:	LED type:	
DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Temperature-controlled fan Control: Stand-alone; DMX Preprogrammed in: Light'J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Colorchief Projection: Flicker-free Beam angle: 7° - 48° Beam angle (1/2 peak): 1 4 - 48° Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise- sensitive environments) Legal specifications Special product:	DMX channels:	5; 6; 7
Cooling: Temperature-controlled fan Control: Stand-alone; DMX Preprogrammed in: Light 'J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Colorchief Projection: Flicker-free Beam angle: 7° - 48° Beam angle (1/2 peak): 14 - 48° Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise- sensitive environments) Legal specifications Special product:	DMX input:	1 x 3-pin XLR (M) mounting version
Control: Stand-alone; DMX Preprogrammed in: Light'J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Colorchief Projection: Flicker-free Beam angle: 7° - 48° Beam angle (1/2 peak): 7 - 39° Beam angle (1/10 peak): 14 - 48° Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise- sensitive environments) Legal specifications Special product:	DMX output:	1 x 3-pin XLR (F) mounting version
Preprogrammed in: Light'J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Colorchief Projection: Flicker-free Beam angle: 7° - 48° Beam angle (1/2 peak): 7 - 39° Beam angle (1/10 peak): 14 - 48° Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise- sensitive environments) Legal specifications Special product:	Cooling:	Temperature-controlled fan
OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Colorchief Projection: Flicker-free Beam angle: 7° - 48° Beam angle (1/2 peak): 7 - 39° Beam angle (1/10 peak): 14 - 48° Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Legal specifications Special product:	Control:	Stand-alone; DMX
Beam angle:7° - 48°Beam angle (1/2 peak):7 - 39°Beam angle (1/10 peak):14 - 48°Housing color:BlackAttachment system:Mounting bracketDisplay type:LCD displayDimensions:Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cmWeight:3,74 kgNoise classification:Class 1 (very slight noise, suitable for noise-sensitive environments)Legal specificationsSpecial product:	Preprogrammed in:	OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain;
Beam angle (1/2 peak): 7 - 39° Beam angle (1/10 peak): 14 - 48° Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Legal specifications Special product:	Projection:	Flicker-free
Beam angle (1/10 peak): 14 - 48° Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Legal specifications Special product:	Beam angle:	7° - 48°
Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Legal specifications Special product:	Beam angle (1/2 peak):	7 - 39°
Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Legal specifications Special product:	Beam angle (1/10 peak):	14 - 48°
Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Legal specifications Special product: Not designed for household room illumination	Housing color:	Black
Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Legal specifications Special product:	Attachment system:	Mounting bracket
Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Legal specifications Special product: Not designed for household room illumination	Display type:	LCD display
Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Legal specifications Special product: Not designed for household room illumination	Dimensions:	Width: 19,6 cm
sensitive environments) Legal specifications Special product: Not designed for household room illumination	Weight:	3,74 kg
Special product: Not designed for household room illumination	Noise classification:	
	Legal specifications	
Intended use: Show effect lighting	Special product:	Not designed for household room illumination
	Intended use:	Show effect lighting